SAŠA BOŽOVIĆ PR USLUGE SISTEMA OBEZBEĐENJA PC BOOM BOOM BEDINA VAROŠ
32250 Ivanjica, 13. Septembar br.30
Tel: 060/386-09-09
E-mail: office@pcboomboom.rs

LAN MK TP-LINK ARCHER T2U AC600 WIRELESS 600MB/S DUAL BAND USB

Naziv:	LAN MK TP-LINK ARCHER T2U AC600 WIRELESS 600MB/S DUAL BAND USB
Slika:	
Šifra:	#BM4366881733544136847
Barkod:	6935364089917
Proizvođač:	TP-LINK

Detalji

Kategorija:	MREŽNE KARTICE
Oznake:	Proveri dostupnost
Atributi:	INTERFEJS: USB

Cena

Cena sa PDV:	2,615.20 RSD *WEB CENA 2,876.72 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

HARDWARE FEATURES	
Interface	USB 2.0
LED	Status
Dimensions (W x D x H)	1.6×0.7×0.3 in. (41×19.5×8.7mm)
Antenna Type	Omni Directional

WIRELESS FEATURES	
Wireless Standards	IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	5GHz 2.4GHz
Signal Rate	5GHz 11ac: Up to 433Mbps(dynamic) 11n: Up to 150Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz 11n: Up to 150Mbps(dynamic) 11g: Up to 54Mbps(dynamic)

	11b: Up to 11Mbps(dynamic)
Reception Sensitivity	5GHz : 11a 6Mbps: -94dBm 11a 54Mbps: -78dBm 11n HT20 MCS0: -94dBm 11n HT20 MCS7: -77dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -74dBm 11ac VHT80 MCS0: -89dBm 11ac VHT80 MCS9: -64dBm 2.4GHz: 11b 1Mbps: -99dBm 11b 11Mbps: -91dBm 11g 6Mbps: -94dBm 11g 54Mbps: -77dBm 11n HT20 MCS0: -95dBm 11n HT20 MCS7: -76dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -73dBm
Transmit Power	<20dBm (EIRP)
Wireless Modes	Ad-Hoc / Infrastructure mode
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Modulation Technology	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

OTHERS	
Certification	FCC, RoHS
Package Contents	Wireless Adapter Archer T2U Resource CD Quick Installation Guide
System Requirements	Windows & MacOS
Environment	Operating Temperature: 0℃~40℃ (32℉~104℉) Storage Temperature: -40℃~70℃ (-40℉~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing