

MATIČNA PLOČA 1700 GIGABYTE Z790 D AX

Naziv: MATIČNA PLOČA 1700 GIGABYTE Z790 D AX

Slika:



Šifra: #BM811801734148965275

Barkod: 4719331860592

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake: [Proveri dostupnost](#)Atributi: M.2: DA
PODRŽANA MEMORIJA: DDR5
CHIPSET: Z790
PROCESORSKO LEŽIŠTE: LGA 1700**Cena**Cena sa PDV: 29,990.00 RSD *WEB CENA
32,989.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte Z790 D AX DDR5 LGA1700 ATX Matična ploča
Procesorsko podnožje (Socket)	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel Z790
Podrška za procesore	14th, 13th, and 12th Generation Intel Core, Pentium Gold and Celeron Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	14th and 13th Generation Intel Core i9/i7 Processors: - Support for DDR5 7600(O.C.)

	Podrška za memorije	/7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600 / 5400 / 5200/ 4800/4400 MT/s memory modules 13th Generation Intel Core i5/i3 and 12th Generation Intel Core, Pentium Gold and Celeron Processors: - Support for DDR5 4800/4400 MT/s memory modules 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
	Podrška za grafiku - portovi	Integrated Graphics Processor-Intel HD Graphics support: - 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version and HDCP 2.3. Support for native HDMI 2.1 TMDS compatible ports. - 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz
	Slotovi za proširenja	CPU: - 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16) The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset: - 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4) - 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x1 (PCIEX1_4) - 2 x PCI Express x1 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_2, PCIEX1_3)
	M.2 portovi	3x M.2 Socket 3
	Čuvanje podataka - portovi	CPU: - 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset: - 1 x M.2 connectors (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB) - 1 x M.2 connectors (Socket 3, M key, type 2280 SATA and PCIe 4.0 x4/x2 SSD support) (M2M_SB) - 4 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
	SATA portovi	4x SATA 6Gb/s

LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	Intel Wi-Fi 6E AX211 (PCB rev. 1.0) - WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands - BLUETOOTH 5.3 - Support for 11ax 160MHz wireless standard
Bluetooth	5.3
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel 7.1-channel audio, access the audio software for audio settings. Support for S/PDIF Out
USB portovi	Chipset: - 1 x USB Type-C port on the back panel, with USB 3.2 Gen 2 support - 1 x USB Type-C port with USB 3.2 Gen 1 support, available through the internal USB header - 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel - 6 x USB 3.2 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header) - 2 x USB 2.0/1.1 ports on the back panel Chipset+USB 2.0 Hub: - 4 x USB 2.0/1.1 ports, available through the internal USB headers
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port 1 x USB Type-C port, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 2 Type-A port (red) 4 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 2 x SMA antenna connectors (2T2R) 1 x HDMI port 1 x DisplayPort 1 x RJ-45 port 3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x CPU fan header 1 x CPU fan/water cooling pump header 3 x system fan headers 1 x system fan/water cooling pump header 2 x addressable LED strip headers 3 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 1 x USB Type-C header, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 2 x Thunderbolt add-in card connectors 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x reset button 1 x Q-Flash Plus button

	1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control Norton Internet Security (OEM version) LAN bandwidth management software
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	ATX
Prava potrošača:	Zakonska saobraznost 2 godine
EAN:	4719331860592