

TENDA TEG1116P-16-150W LAN 16-PORT 10/100/1000M BASE-TX ETHERNET PORTS SWITCH

Naziv: TENDA TEG1116P-16-150W LAN 16-PORT
10/100/1000M BASE-TX ETHERNET PORTS SWITCH

Slika:



Šifra: #BM346931739874711797

Barkod: 6932849431360

Proizvođač: TENDA

Detalji

Kategorija: LAN RUTERI

Oznake: [Proveri dostupnost](#)

Atributi:

Cena

Cena sa PDV: 29,630.30 RSD *WEB CENA
32,593.33 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

TEG1116P-16-150W is a Tenda PoE Switch that offers 16 10/100/1000Mbps Base-TX RJ45 ports 1-16 comply with IEEE 802.3af standard (maximum PoE power output: 15.4 W) and 802.3at standard (maximum PoE power output: 30 W). The switch offers a maximum PoE power output of 135W and can supply power to and exchange data with APs, IP cameras and IP phones through CAT5 cables. It also provides simple management modes such as CCTV, VLAN and isolation to help reduce cabling costs of IP terminals like APs and IP cameras.

Standard&Protocol IEEE 802.3/IEEE 802.3u/IEEE 802.3ab/IEEE 802.3x/IEEE 802.3af/IEEE 802.3atIndicator16*Link/Act per device16*PoE per device1*Power per deviceInterface16 10/100/1000 Base-T ports(Data/Power)Lightning Protection 6KVStore & Forward Yesexchange capacity 32 GbpsPacket Forwarding Rate 23.6MppsRAM Data Buffer4MbMAC Address Table 4KPoE supply management Port 1-16 support IEEE802.3at/af PoE standardPoE through pin1 2 4 5 +3 6 7 8 -Input Voltage AC: 100-240V~50/60HzDimension 294*178*44mm (W x D x H)Power Consumption in full con guration:<150WPoE Max Power Supply:135WPort FeaturesStandard: the switch functions as a common unmanaged switch and all the ports of the switch can communicate with each other.CCTV: the port cache is optimized and PoE ports 1-8 have higher priorities over the other ports. All the ports of the switch can communicate with each other.VLAN: ports 1 to 14 are isolated from each other, but can communicate with ports 15 and 16 (uplink ports) respectively.Isolation: ports 1 to 8 and Ports 9 to 16 belong to two di erent VLAN.This mode can be used to isolate supervision network and wireless network to make them not interfere with each other.Environment Operating Temperature: 0?~40? (32?~104?)Storage Temperature: -40?~70? (-40?~158?)Operating Humidity: 10%~90% non-condensingStorage Humidity: 5%~90% non-condensing