SAŠA BOŽOVIĆ PR USLUGE SISTEMA OBEZBEĐENJA PC BOOM BOOM BEDINA VAROŠ
32250 Ivanjica, 13. Septembar br.30
Tel: 060/386-09-09
E-mail: office@pcboomboom.rs

IP-COM G1024D LAN 24-PORT 10/100/1000M BASE-T ETHERNET PORTS (MDI/MDIX) DESK/RACK MOUNT(ALT=TEG1024D

Naziv:	IP-COM G1024D LAN 24-PORT 10/100/1000M BASE-T ETHERNET PORTS (MDI/MDIX) DESK/RACK MOUNT(ALT=TEG1024D
Slika:	
Šifra:	#BM4076931739874958551
Barkod:	6932392831501
Proizvođač:	IP-COM

Detalji

Kategorija:	LAN RUTERI
Oznake:	Proveri dostupnost
Atributi:	

Cena

Cena sa PDV:	11,722.42 RSD *WEB CENA 12,894.66 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:	Compliant with IEEE802.3, IEEE802.3u, IEEE802.3X, IEEE802.3ab standards24*10/100/1000 Mbps auto-negotiation RJ45 portsAuto MDI/MDIX8000 MAC address and MAC auto Learning & Auto AgingIEEE 802.3x full duplex flow control, and backpressure half duplex flow control48 Gbps switching fabric for non-blocking line-speed forwardingLED indicators for indicating working status and troubleshootingBuilt-in power supply system with 6 kV common mode and 4 kV differential mode lightning protection24 ports with 6 kV common mode lightning protectionIP camera connectionPlug and playIP-COM G1024D is a 24-port gigabit unmanaged desktop/rack switch designed for video surveillance, offices, work groups, and SMEs for easy, economical and high-speed internet purposes. Its full duplex transmission rate can reach up to 2000 Mbps, ensuring the timely transfer of large files as well as smooth streaming videos. The professional integrated lightening protection circuit, the built-in power supply module, and all the 24 ports could withstand 6 kV lightning surge, ensuring the switch to run stably. G1024D is your ideal choice for extension, or upgrade to high-speed and stable gigabit optical network.Stable connection for 7*2424*10/100/1000 Mbps auto-negotiation RJ45 ports, up to 2000 Mbps of full duplex transmission rate, line-speed forwarding by all ports, and large cache capacity ensure the timely transfer of large files and stable streaming video. Stay connected for 7*24.Excellent lightning protection of portsProfessional integrated lightning protection circuit enables all the 24 ports to provide IV-class (6 kV in common mode) lightning protection, effectively decreasing the damage rate to the ports by lightning surge.Professional lightning protection for power supplyThe built-in power supply module is designed with enhanced lightning protection, which can withstand 6 kV lightning surge, 3 times higher than other ordinary switches, effectively protecting the switch from being damaged by adverse thunderstorm.Innovative designFull steel housing and plating through holes in three faces allow higher-efficient heat dissipation; fanless design ensures the noiselessness and dust free, harmoniously fitting into the offices; 13-inch size makes it mountable both on desktop and rack and plug and play function makes it easy for use.Standard&Protocol IEEE 802.3?IEEE 802.3u?IEEE 802.3x?IEEE 802.3abForwarding Speed 10Mbps : 14880pps100Mbps : 148800pps1000Mbps : 1488000ppsTransmission Media 10BASE-T: UTP category 3, 4, 5 cable100BASE-TX/1000BASE-T: UTP category 5, 5e or above cablePort 24*10/100/1000Mbps auto-negotiation RJ 45 ports (Auto MDI/MDIX)LED Indication 24* Link/Act indicator,1*power indicatorDimensions 297mm×178mm×44mmSwitch Feature Store-and-ForwardMAC auto Learning & Auto Aging8K MAC48Gbps Backpanel bandwidthLighting Proof lightning protection 6KV for power supply,6KV for all portsPower Input 100~240V AC,50/60HzOperating Environment Temperature:0?~45?Humidity:10%~90% non-condensingStorage Environment Temperature:-40?~70?Humidity:5%~90% non-condensingTenda