

TENDA O3 OUTDOOR LONG RANGE POINT TO POINT CPE 2.4GHZ 150MBPS, 12DBI, 5KM

Naziv: TENDA O3 OUTDOOR LONG RANGE POINT TO POINT
CPE 2.4GHZ 150MBPS, 12DBI, 5KM



Šifra: #BM346901739880738163

Barkod: 6932849429015

Proizvođač: TENDA

Detalji

Kategorija: RUTERI

Oznake: [Proveri dostupnost](#)

Atributi:

Cena

Cena sa PDV: 7,934.76 RSD *WEB CENA
8,728.24 RSD *Cena za odloženo web plaćanje

Ostalo

Opis: O3 2.4GHz Outdoor CPE is designed to WISP CPE solutions and long distance wireless network solutions for video surveillance and data transmission. It features with 12dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network. Adopt of auto-bridging technology,two CPE can connect to each other automatically to make it easy to setup• 2.4GHz 11n 150Mbps• 12dbi directional antenna• IP64 waterproof enclosure• 6000V Lightning Protection• AP,Station,WISP operating mode supported• Up to 60 meters of flexible deployment with included PoE Injector5km+ transmission RangeO3 adopts of independent power amplifier and 12dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network up to 5km.Auto-bridge For Two DeviceO3 adopts of auto-bridge technology,two cpe can connect to each other when you power on them face to face. It is very easy to setup for CCTV surveillance and data.Smart Signal Indicator LED3 signal LED Lights represent the currently signal strength that O3 receives from peer device.It is helpful to find the right location to deploy the device and achieve a better performance.Professional Outdoor DesignEquipped with IP64 waterproof enclouse and high quality hardware design, O3 can work in various weather conditions, such as sunshine, rainfall or extremely

low/high temperature environment Long-Distance
Wireless Connection One work as AP mode and another
work as Station mode to create a long distance
wireless connection for video surveillance and data
transmission. WISP (Client+Router) Mode Wirelessly
connect to WISP station/hotspot to share Internet to
local wireless and wired network Dimension
270*94.86*67.5mm Deployment Pole Mount/Wall
Mount Application Scenarios PtP and PtMP wireless
connection for Private ISP access or CCTV
Surveillance Frequency Range: 2.4GHz Compliant
Standards: IEEE 802.11b/g/n Maximum Wireless Rate:
150Mbps Interfaces: 2*10/100Mbps Ethernet
Port Antenna Polarization: Horizontal
Polarization Antennas Gain: 12dbi Antenna Beamwidth:
Horizontal: 60° Vertical: 30° GND: 1*GND 1*Reset
Button Power Consumption: 4.3W Waterproof Level:
IP65 LED Indicator: PoE/LAN, LED1, LED2, LED3 Power
Method: 12V1A Passive PoE Lightning Protection:
6000V Passive PoE: Passive power over ethernet via
PoE/LAN (+4,5pins-7,8pins) Voltage range: 9-13.8V
DC Reception Sensitivity 11b 1Mbps
-92dBm ±1.5dBm 11n MCS0: -92±1.5dBm 11n MCS7:
-72±1.5dBm Operating mode:
AP/Station/WISP/P2MP/WDS
Repeater/Router Enable/Disable Wireless Radio:
Support SSID Hidden: Support Wireless Client isolation:
Support SSID Isolation: Support Channel Bandwidth:
20/40MHz Channel Shift: /Wireless Access Control:
Support Weak Signal Client Limitation:
Support Transmission Power: Adjustable power by
1dBm WMM Capable: Support APSD Capable:
Support Wireless Security: 64/128 WEP, WPA-PSK, WPA2-
PSK, WPA&WPA2-PSK, WPA, WPA2 Transparent Bridge:
Support VLAN Tagging for SSID: Support DHCP Server:
Support VPN Pass-Through: PPTP, L2TP Remote Web
access: Support Schedule Reboot: Support Page
Timeout: Support Ping Watchdog: Support DynDNS: noip,
dyndns.org Network Diagnoses: Ping, Traceroute, Signal
Scan Time: Support Firmware upgrade:
Support Backup/Restore Configuration:
Support Username Management: Support System Logs:
Support Managed By Controller: PC Software CPE
Assistant Package Contents 1*2.4GHz 11n 12dBi
150Mbps outdoor CPE 031*Power Adapter 1*PoE
Injector 1*Quick Installation Guide Operation
Temperature -30° ~ 60° Storage Temperature -40° ~
70° Operating Humidity 10%~90% non-
condensing Storage Humidity 10%~90% non-
condensing Default login IP 192.168.2.1 Default Login
Username: admin Default Login Password:
admin Certification: FCC/CE/RoHS