

DAHUA DH-SD2A500HB-GN-AW-PV-0400-S2 5MP STARLIGHT 30M ANALITIKA AKTIVNO ODVRACANJE

Naziv: DAHUA DH-SD2A500HB-GN-AW-PV-0400-S2 5MP
STARLIGHT 30M ANALITIKA AKTIVNO ODVRACANJE

Slika:



Šifra: #BM2679941739888040123

Barkod: 6923169711317

Proizvođač: DAHUA

Detalji

Kategorija: KAMERE

Oznake: [Proveri dostupnost](#)

Atributi:

Cena

Cena sa PDV: 20,580.91 RSD *WEB CENA
22,639.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:	DAHUA SD2A500HB-GN-AW-PV-0400-S2WiFi 5MP IP IC + BS PT kameraLight serija1/2.8" 5MP Starvis™ CMOS, progresivno skeniranjeStarlightEfektivni broj piksela 2560 (H) × 1920 (V)Osetljivost 0.005 Lux@F1.6 (kolor), 0.0005 Lux@F1.6 (C/B), 0Lux (IC aktivan)IC LE diode dometa cca. 30m, beli LED dometa cca. 30m, tri moda rada iluminatoraFiksni objektiv 4mm F1.6, vidni ugao 80.4° horizontalnoOpseg horizontalne rotacije 0°-345°, opseg vertikalne rotacije 0° do +80°Brzina horizontalne rotacije do 74°/sDo 300 preset pozicijaAnalitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani regionDetekcija ljudiFunkcija aktivnog odvracanjaH.265, H.264, H.264B, MJPEG kompresijaSmart codec podrškaDual streamPodržane rezolucije do 5M, frame rate do 20fps u 5M, do 25/30fps u 4M i nizim rezolucijamaBitrate H.264 512~8192 kbps, 233~7680 kbpsBLC, HLC, DWDR, 2D + 3D DNRUgrađen mikrofoni i zvucnik, dvosmerni audioAudio I/O x1Micro SD slot (do 512GB)WiFi 2.4 GHz 150Mbps (802.11n, IEEE802.11b, 802.11g)RJ45 10/100 Base-T mrežni portProtokoli: UDP, FTP, RTMP, IPv6, IPv4, IP Filter, DNS, RTCP, HTTP, NTP, SSL, DHCP, RTP, SMTP, HTTPS, TCP/IP, RTSP, DDNS, ARPInteroperabilnost: RTMP, CGI, SDK, ONVIF (Profile S&T), P2PDimenzije 140.5mm × 111.0mmMasa 0.5kgIP66 stepen zaštiteOpseg radne temperature - 30°C do +55°C2000V prenaponska zaštitaPotrebno napajanje PoE (802.3af) ili 12VDC/1.5 A ± 10%Potrošnja 11WU kompletu sa nosačem za plafonsku/zidnu montažuCE: EN55032/EN50130-4/EN, IEC61000-3-3/EN, IEC61000-3-2/EN5024/EN55035/EN62368-1, FCC: 47 CFR FCC Part15, Subpart B, ANSI C63.4:2014
-------	--