

MB AM5 ASROCK B650M-HDV/M.2

Naziv: MB AM5 ASROCK B650M-HDV/M.2

Slika:



Šifra: #BM42511801742875491229

Barkod: 4710483942693

Proizvođač: ASROCK

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

Atributi: PROCESORSKO LEŽIŠTE (SOCKET): AMD AM5
UKUPNO USB PRIKLJUČAKA: 15
TIP MEMORIJE: DDR5
MEMORIJSKI SLOTOVI: 4 X DDR5
MAKSIMALNA KOLIČINA MEMORIJE: 64
FORMAT: MICRO ATX**Cena**Cena sa PDV: 12,915.35 RSD *WEB CENA
14,206.89 RSD *Cena za odloženo web plaćanje**Ostalo**Opis:

- CPU
 - Supports AMD Socket AM5 Ryzen™ 7000 Series Processors
- Chipset
 - AMD B650
- Memory
 - Dual Channel DDR5 Memory Technology
 - 2 x DDR5 DIMM Slots
 - Supports DDR5 non-ECC, un-buffered memory up to 6400+(OC)
 - Max. capacity of system memory: 64GB
 - Supports Extreme Memory Profile (XMP) and EXTENDED Profiles for Overclocking (EXPO) memory modules
- BIOS
 - 256Mb AMI UEFI Legal BIOS with GUI support
- Graphics
 - Integrated AMD RDNA™ 2 graphics (Actual support may vary by CPU)
 - 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz
 - 1 x DisplayPort 1.4 with DSC (compressed), supports HDCP 2.3 and max. resolution up to

- 4K 120Hz
 - Audio
 - 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
 - Nahimic Audio
 - LAN
 - 2.5 Gigabit LAN 10/100/1000/2500 Mb/s
 - Dragon RTL8125BG
 - Supports Dragon 2.5G LAN Software
 - Smart Auto Adjust Bandwidth Control
 - Visual User Friendly UI
 - Visual Network Usage Statistics
 - Optimized Default Setting for Game, Browser, and Streaming Modes
 - User Customized Priority Control
- Slots
 - CPU:**
 - 1 x PCIe 4.0 x16 Slot (PCIE1), supports x16 mode*
 - 1 x PCIe 4.0 x16 Slot (PCIE3), supports x4 mode*
 - Chipset:**
 - 1 x PCIe 4.0 x1 Slot (PCIE2)*
 - 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module
 - Supports AMD CrossFire™
 - 15µ Gold Contact in VGA PCIe Slot (PCIE1)
- *Supports NVMe SSD as boot disks
- Storage
 - CPU:**
 - 1 x Blazing M.2 Socket (M2_1, Key M), supports type 2280 PCIe Gen5x4 (128 Gb/s) mode*
 - Chipset:**
 - 1 x Hyper M.2 Socket (M2_2, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*
 - 4 x SATA3 6.0 Gb/s Connectors
 - *Supports NVMe SSD as boot disks
- RAID
 - Supports RAID 0, RAID 1 and RAID 10 for SATA storage devices
 - Supports RAID 0, RAID 1 and RAID 10 for M.2 NVMe storage devices*
- *Requires additional M.2 NVMe expansion cards to support RAID 10
- USB
 - 1 x USB 3.2 Gen2 Type-C (Front)
 - 1 x USB 3.2 Gen1 Type-C (Rear)
 - 6 x USB 3.2 Gen1 Type-A (2 Rear, 4 Front)
 - 8 x USB 2.0 (4 Rear, 4 Front)
- *All USB ports support ESD Protection
- Connector
 - 1 x SPI TPM Header
 - 1 x Power LED and Speaker Header
 - 1 x CPU Fan Connector (4-pin)*
 - 3 x Chassis/Water Pump Fan Connectors (4-pin) (Smart Fan Speed Control)**
 - 1 x 24 pin ATX Power Connector
 - 1 x 8 pin 12V Power Connector
 - 1 x Front Panel Audio Connector
 - 1 x Thunderbolt™ AIC Connector (5-pin) (Supports ASRock Thunderbolt™ 4 AIC Card)
 - 2 x USB 2.0 Headers (Support 4 USB 2.0 ports)
 - 2 x USB 3.2 Gen1 Headers (Support 4 USB 3.2 Gen1 ports)
 - 1 x Front Panel Type C USB 3.2 Gen2 Header
- *CPU_FAN1 supports the fan power up to 1A

(12W).

**CHA_FAN1~3/WP support the fan power up to 2A (24W).

CHA_FAN1~3/WP can auto detect if 3-pin or 4-pin fan is in use.

- Rear Panel I/O
 - 2 x Antenna Mounting Points
 - 1 x HDMI Port
 - 1 x DisplayPort 1.4
 - 1 x USB 3.2 Gen1 Type-C Port
 - 2 x USB 3.2 Gen1 Type-A Ports
 - 4 x USB 2.0 Ports
 - 1 x RJ-45 LAN Port
 - 1 x BIOS Flashback Button
 - HD Audio Jacks: Line in / Front Speaker / Microphone
- Software and UEFI
 - Software**
 - ASRock Motherboard Utility (A-Tuning)
 - ASRock Dragon 2.5G LAN Software*
 - UEFI**
 - ASRock Full HD UEFI
 - ASRock Auto Driver Installer
 - ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.

- Accessories
 - 1 x User Manual
 - 2 x SATA Data Cables
 - 2 x Screws for M.2 Sockets
- Form Factor
 - Micro ATX Form Factor: 9.6-in x 8.9-in, 24.4 cm x 22.6 cm
 - 2oz Copper PCB