

MATIČNA PLOČA AM5 GIGABYTE B850I AORUS PRO DDR5 HDMI/M.2

Naziv: MATIČNA PLOČA AM5 GIGABYTE B850I AORUS PRO
DDR5 HDMI/M.2

Slika:



Šifra: #BM811801747364465057

Barkod: 4719331867263

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

Atributi: PROCESORSKO LEŽISTE: AM5
CHIPSET: B850
M.2: DA
PODRŽANA MEMORIJA: DDR5

Cena

Cena sa PDV: 35,990.00 RSD *WEB CENA
39,589.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

Model	Gigabyte B850I AORUS PRO Wi-Fi7 AM5 DDR5 Mini-ITX Matična ploča
Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD B850
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	Support for DDR5 8400(OC) / 8200(OC) / 8000(OC) / 7800(OC) / 7600(OC) / 7200(OC) / 7000(OC) / 6800(OC) / 6666(OC) / 6600(OC) /

	Podrška za memorije	6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s memory modules 2 x DDR5 DIMM sockets supporting up to 128 GB (64 GB single DIMM capacity) of system memory Dual channel memory architecture Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for AMD EXTended Profiles for Overclocking (AMD EXPO) and Extreme Memory Profile (XMP) memory modules
	Podrška za grafiku - portovi	Integrated Graphics Processor with AMD Radeon Graphics support: - 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version and HDCP 2.3, and HDR. Support for native HDMI 2.1 TMDS compatible ports.
	Slotovi za proširenja	1 x PCI Express x16 slot, integrated in the CPU: - AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x16 mode - AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode - AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode
	M.2 portovi	2x M.2 Socket 3
	Čuvanje podataka - portovi	1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 2280 SSDs: - AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs - AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs - AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs 1 x M.2 connector on the back of the motherboard (M2C_SB), integrated in the Chipset, supporting Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSDs 2 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices
	SATA portovi	2x SATA 6Gb/s
	LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
	Bežična mreža	Realtek Wi-Fi 7 RTL8922AE - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard (Actual data rate may vary depending on environment and equipment.)

Bluetooth	5.4
Zvuk (Audio)	Realtek ALC4080 CODEC High Definition Audio 2-channel
USB portovi	CPU: - 1 x USB Type-C port on the back panel, with USB 3.2 Gen 2 support - 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel Chipset: - 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header - 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) - 4 x USB 2.0/1.1 ports (2 ports on the back panel, 2 ports available through the internal USB header)
Konektori na zadnjoj strani	1 x Q-Flash Plus button 1 x HDMI port 2 x antenna connectors (2T2R) 1 x USB Type-C port, with USB 3.2 Gen 2 support 2 x USB 3.2 Gen 2 Type-A ports (red) 2 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x RJ-45 port 2 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 1 x CPU fan/water cooling pump header 1 x system fan header 2 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 2 x M.2 Socket 3 connectors 2 x SATA 6Gb/s connectors 1 x front panel header 1 x speaker header 1 x front panel audio header (routed from the adapter card on the rear panel) 1 x USB Type-C header, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x reset jumper 1 x Clear CMOS jumper 1 x chassis intrusion header
Posebne mogućnosti	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control
Operativni sistem	Windows 11

BIOS

1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS
2.7, ACPI 5.0

Format

Mini-ITX