

MATIČNA PLOČA 1700 ASUS PRIME Z790M-PLUS DP/HDMI/M.2 DDR5

Naziv: MATIČNA PLOČA 1700 ASUS PRIME Z790M-PLUS DP/HDMI/M.2 DDR5



Šifra: #BM7611801749006263921

Barkod: 4711387025741

Proizvođač: ASUS

Detalji

Kategorija: MATIČNE PLOČE

Oznake: [Proveri dostupnost](#)

Atributi: PROCESORSKO LEŽIŠTE: LGA 1700
CHIPSET: Z790
PODRŽANA MEMORIJA: DDR5

Cena

Cena sa PDV: 29,490.00 RSD *WEB CENA
32,439.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:	Tip procesora	Procesorsko ležište (socket) Intel 1700 Čipset intel Z790
	Format ploče	Format microATX Dimenzije 244mm x 244mm Fiksirajući otvori 8 Pakovanje 2x SATA kabl
	Memorija	Tip memorije DDR5 Memorijski slotovi 4x DDR5 Podržane memorije 6.000MHz (O.C.), 5.800MHz (O.C.), 6.200MHz (O.C.), 4.800Mhz, 5.200Mhz, 5.600MHz, 5.400MHz, 6.600MHz (O.C.), 6.800MHz (O.C.), 7.000MHz (O.C.), 6.400MHz (O.C.), 7.200MHz (O.C.), 5.000Mhz Maksimalna ukupna memorija 128GB Ostale osobine Podrška za Extreme Memory Profile (XMP), Dvokanalni (Dual-channel) režim rada memorije, Podrška za non-ECC UDIMM memory, OptiMem II
		PCI Express x16 slot 1x PCI Express 4.0, 1x PCI Express 5.0

Slotovi za proširenje	PCI Express x1 slot 2x PCI Express 4.0 PCI slot 4 Ostali slotovi 3x M.2 slot, 4x SATA III Skladišni interfejs SATA priključci (ukupno) 4 SATA priključci 4x SATA III Ostali skladišni interfejs 3x M.2 RAID RAID 0, RAID 1, RAID 5, RAID 10 Napomena RAID 0, RAID 1 i RAID 10 podrška za SATA priključke
Zvučna kartica	Broj kanala 8 (7.1) Model Realtek® Napomena Audio Shielding, Dedicated audio PCB layers, Premium audio capacitors, Jack-detection, Multi-streaming, Front Panel Jack-retasking, Supports up to 24-Bit/192 kHz playback
Ostalo	Mreža Žična mreža (LAN) 1x 10/100/1.000Mbps (Gigabit ethernet) Model Intel® Priključci na zadnjem panelu DisplayPort priključci 1x DisplayPort 1.4 HDMI priključci 1x HDMI 2.1 Ukupno USB priključaka 8 Ukupno USB C priključaka 1 USB 3.2 priključci 4 (Tip A) Gen1, 1 (Tip A) Gen2, 1 (Tip C) Gen2x2 USB 2.0 priključci 2 (Tip A) RJ-45 (LAN) 1 Audio 3x 3.5mm Unutrašnji priključci Naponski priključci 1 x 24 pin ATX Power Connector, 1 x 8-pin ATX 12V power connector, 1 x 4-pin ATX 12V power connector USB 3.2 1 (podrška za 2 USB 3.2 Gen 1 porta), 1 (podrška za 1 USB 3.2 Gen 1 Tip C porta) USB 2.0 2 (podrška za 4 USB 2.0 porta) Audio 1x Front panel header, 1x S/PDIF izlaz Serijski port 1 Ostali priključci 1 x 4-pin AIO Pump header, 1 x 4-pin CPU OPT Fan header, 1 x 20-3 pin System Panel header with Chassis intrude function, 1 x 4-pin Chassis Fan header, 1 x 4-pin CPU Fan header, 1 x 14-1 pin SPI TPM header, 1 x Clear CMOS header, 3 x Addressable Gen 2 headers, 1 x AURA RGB header, 1 x M.2 slot (Key E), 1 x Thunderbolt™ (USB4®) header Napomena Za iskorišćavanje određenih internih konektora potrebni su dodatni bracket-i ili priključci na kućištu Ostale karakteristike Podržane tehnologije AURA Sync, DIGI+VRM, ASUS CrashFree BIOS 3, ASUS EZ Flash 3, ASUS UEFI BIOS EZ Mode, LANGuard, Overvoltage Protection, Q-DIMM, Q-Slot, Q-LED Core, SafeSlot Core+, Stainless-Steel Back I/O, AI Cooling II