

**MATICNA PLOCA 1700 GIGABYTE B760M D3HP WIFI6 DDR5 VGA/HDMI/DP/M.2**Naziv: MATICNA PLOCA 1700 GIGABYTE B760M D3HP WIFI6  
DDR5 VGA/HDMI/DP/M.2

Slika:



Šifra: #BM811801755399751912

Barkod: 4719331867638

Proizvođač: GIGABYTE

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake: [Proveri dostupnost](#)

Atributi:

**Cena**Cena sa PDV: 14,990.00 RSD \*WEB CENA  
16,489.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

<b>CPU</b>	LGA1700 socket: Supports 14th, 13th, and 12th Generation Intel® Core™, Pentium® Gold, and Celeron® Processors (Check GIGABYTE's website for the latest CPU support list.) L3 cache varies with CPU
<b>Chipset</b>	Intel® B760 Express Chipset
<b>Memory</b>	14th & 13th Gen Intel® Core™ i9/i7: DDR5 5600/5200/4800/4400 MT/s; 13th Gen Intel® Core™ i5/i3 & 12th Gen Intel® Core™, Pentium® Gold, and Celeron®: DDR5 4800/4400 MT/s
	4 x DDR5 DIMM sockets, up to 192 GB (48 GB per DIMM)
	Dual channel memory architecture
	Supports ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (non-ECC mode)

	Supports non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
	Supports Extreme Memory Profile (XMP)
<b>Onboard Graphics</b>	Intel® HD Graphics support
	1 x D-Sub (1920x1200@60Hz max), 1 x HDMI (4096x2160@60Hz max) with HDMI 2.1 and HDCP 2.3
	1 x DisplayPort (4096x2304@60Hz max), DisplayPort 1.2 and HDCP 2.3
	Supports up to triple-display
<b>Audio</b>	Realtek® Audio CODEC, High Definition Audio, 2/4/5.1/7.1-channel
	Supports S/PDIF Out
<b>LAN</b>	Realtek® GbE LAN chip (1 Gbps/100 Mbps/10 Mbps)
<b>Wireless Communication</b>	Realtek® Wi-Fi 6 RTL8851BE: WIFI a/b/g/n/ac/ax, 2.4/5 GHz frequency, Bluetooth 5.3
	Supports 11ax 80MHz wireless standard
<b>Expansion Slots</b>	1 x PCIe x16 (PCIe 4.0, x16) for graphics or NVMe SSD
	2 x PCIe x1 (PCIe 3.0, x1)
<b>Storage Interface</b>	1 x M.2 (Socket 3, M Key, 2280 PCIe 4.0 x4/x2 SSD)
	1 x M.2 (Socket 3, M Key, 2280 PCIe 4.0 x4/x2 SSD)
	4 x SATA 6Gb/s
	RAID 0, RAID 1, RAID 5, RAID 10 support
<b>USB</b>	1 x USB Type-C® (USB 3.2 Gen 1, internal)
	5 x USB 3.2 Gen 1 (3 on the back panel, 2 internal)
	2 x USB 2.0/1.1 ports (back panel)
	4 x USB 2.0/1.1 ports (internal)
<b>Internal I/O Connectors</b>	1 x 24-pin ATX main power connector
	1 x 8-pin ATX 12V power connector
	1 x CPU fan header
	3 x system fan headers
	1 x addressable LED strip header

	1 x RGB LED strip header
	2 x M.2 connectors, 4 x SATA 6Gb/s
	1 x front panel header
	1 x USB Type-C® header (USB 3.2 Gen 1)
	2 x USB 2.0/1.1 headers
	1 x Trusted Platform Module (TPM) header
	1 x serial port header
	1 x parallel port header
	1 x S/PDIF Out header
	1 x Q-Flash Plus button
	1 x reset jumper
	1 x Clear CMOS jumper
<b>Back Panel Connectors</b>	2 x USB 2.0/1.1 ports
	1 x PS/2 keyboard/mouse port
	2 x SMA antenna connectors
	1 x D-Sub port
	1 x DisplayPort
	1 x HDMI port
	3 x USB 3.2 Gen 1 ports
	1 x RJ-45 port
	3 x audio jacks
<b>I/O Controller</b>	iTE® I/O Controller Chip
<b>H/W Monitoring</b>	Voltage, Temperature, Fan speed detection, Water cooling flow rate detection, Fan fail warning, Fan speed control (dependent on installed fan)
<b>BIOS</b>	128 Mbit flash, AMI UEFI BIOS
<b>Unique Features</b>	GIGABYTE Control Center (GCC) Support, Q-Flash, Q-Flash Plus
<b>Bundled Software</b>	Norton® Internet Security (OEM), LAN bandwidth management
<b>Operating System</b>	Windows 11 64-bit, Windows 10 64-bit
<b>Form Factor</b>	Micro ATX (24.4 cm x 24.4 cm)