SAŠA BOŽOVIĆ PR USLUGE SISTEMA OBEZBEĐENJA PC BOOM BOOM BEDINA VAROŠ
32250 Ivanjica, 13. Septembar br.30
Tel: 060/386-09-09
E-mail: office@pcboomboom.rs

SSD INTENSO 2.5" SATA3 128GB 3812430

Naziv:	SSD INTENSO 2.5" SATA3 128GB 3812430
Slika:	
Šifra:	#BM4246041762315631061
Barkod:	4034303016679
Proizvođač:	NEDEFINISAN

Detalji

Kategorija:	SSD
Oznake:	
Atributi:	FORMAT: 2,5" KAPACITET DISKA: 128GB

Cena

Cena sa PDV:	3,418.56 RSD *WEB CENA 3,760.42 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:	Features SSD capacity The Solid State Drive's data storage capacity. 128 GB SSD form factor The size of the solid-state drive, given in inches 2.5" Interface Interface ports to connect pieces of equipment. USB (Universal Serial Bus) has become the most popular wired interface to connect peripherals. USB 2.0 supports speeds up to 480 Mbit/s (USB 1: 12 Mbit/s). The interface FireWire is also known as the IEEE 1394 standard. Enhanced IDE (EIDE)is sometimes referred to as Fast ATA, Fast IDE or ATA-2. Serial ATA III NVMe NVM Express (NVMe) or Non-Volatile Memory Host Controller Interface Specification (NVMHCIS) is an open logical device interface specification for accessing non-volatile storage media attached via a PCI Express (PCIe) bus. NVM Express, as a logical device interface, has been designed to capitalize on the low latency and internal parallelism of solid-state storage devices. Memory type Type of memory in the device e.g. DDR3, SRAM (Static RAM). MLC Component for

What this product is used as a part of (component for).
PC/Laptop
Data transfer rate
Rate at which data can be transferred. Usually expressed in units per second. May vary with network configurations.
6 Gbit/s
Read speed
The speed at which a device can read data.
550 MB/s
Write speed
The speed at which a device can write data.
500 MB/s
Random read (4KB)
133120 IOPS
Random write (4KB)
128000 IOPS
Storage drive buffer size
256 MB
S.M.A.R.T. support

TRIM support

Features
Mean time between failures (MTBF)
Statistical model used to indicate product/mechanism reliability; expressed in hours and percentage of duty cycle. This number (in hours) does not indicate the mean time before failure for a single unit/mechanism.
2000000 h
Weight & dimensions
Width
The measurement or extent of something from side to side.
70 mm
Depth
The distance from the front to the back of something.
100 mm
Height
The measurement of the product from head to foot or from base to top.
7 mm
Weight
Weight of the product without packaging (net weight). If possible, the net weight is given including standard accessories and supplies. Please note that sometimes the manufacturer leaves out the weight of accessories and/or supplies.
83 g
Packaging data
Package type
The type of product package e.g. box.
Box
Operational conditions
Operating shock
Environmental requirements for optimal protection from impact in operating mode
1500 G
Other features
Product colour
The colour e.g. red, blue, green, black, white.
Black
Internal
The product is built in.

Connectivity technology
The technology that enables connectivity of the device, e.g. wired or wireless.
Wired
Logistics data
Harmonized System (HS) code
84717070