

MATIČNA PLOČA 1200 GIGABYTE H410M H V2 G20 VGA/HDMI/M.2Naziv: MATIČNA PLOČA 1200 GIGABYTE H410M H V2 G20
VGA/HDMI/M.2

Slika:



Šifra: #BM811801764216230426

Barkod: 4719331815387

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

[Proveri dostupnost](#)

Atributi:

CHIPSET: H410
M.2: DA
PODRŽANA MEMORIJA: DDR4
PROCESORSKO LEŽIŠTE: LGA 1200**Cena**Cena sa PDV: 8,490.00 RSD *WEB CENA
9,339.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Tip procesora	Intel
Podnožje	Intel® 1200
Čipset	Intel® H410
Format ploče	Micro ATX
Podržani procesori	Support for 10th Generation Intel® Core™ i9 processors/Intel® Core™ i7 processors/ Intel® Core™ i5 processors/Intel® Core™ i3 processors/Intel® Pentium® processors/ Intel® Celeron® processors in the LGA1200 package
Podržana memorija	DDR4
	Intel® Core™ i9/i7 processors: Support for DDR4 2933/2666/2400/2133 MHz memory modules Intel® Core™

Memorija	i5/i3/Pentium®/Celeron® processors: Support for DDR4 2666/2400/2133 MHz memory modules 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Integrirana grafička karta	1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz * Support for HDMI 1.4 version and HDCP 2.3.
Slotovi za proširenje	1 x PCI Express x16 slot, running at x16 1 x PCI Express x1 slot (The PCI Express slots conform to PCI Express 3.0 standard.
Storage	1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 PCIe x4/x2 SSD support) 4 x SATA 6Gb/s connectors
Mrežna karta	Gigabit Ethernet Chip (1 Gbps/100 Mbps)
Zvučna karta	Realtek® Audio CODEC High Definition Audio 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.
USB	4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) 6 x USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header)
Konektori na zadnjoj strani	1 x PS/2 keyboard port 1 x PS/2 mouse port 1 x D-Sub port 1 x HDMI port 2 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks
Interni konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 4 x SATA 6Gb/s connectors 1 x CPU fan header 1 x system fan header 1 x RGB LED strip header 1 x front panel header 1 x front panel audio header 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) 1 x serial port header 1 x Clear CMOS jumper * All fan headers are subject to support AIO_Pump, Pump and high performance fan with the capability of delivering up to 2A/12V @ 24W.

Bios	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
------	--