

SERVER DELL POWEREDGE T160 XEON E-2414/16GB/1X2TB/300W

Naziv: SERVER DELL POWEREDGE T160 XEON E-2414/16GB/1X2TB/300W

Slika:



Šifra: #BM512111766117261730

Barkod:

Proizvođač: DELL

Detalji

Kategorija: SERVERI

Oznake: [Proveri dostupnost](#)

Atributi:

Cena

Cena sa PDV: 250,815.00 RSD *WEB CENA
275,896.50 RSD *Cena za odloženo web plaćanje

Ostalo

Opis: Connections and interfaces
Number of USB 2.0 ports
3
Number of Ethernet LAN ports (RJ-45)
2
Number of VGA (D-Sub) ports
1
USB 3.2 Gen 1 (3.1 Gen 1) Number of Type A ports
4
Number of serial ports
1
Services
Remote Management
iDRAC9 Basic 16G
processor
Processor manufacturer
Intel
Processor family
Intel Xeon E
Processor threads
4
Processor clock speed
2.6 GHz
Number of installed processors
1
processor
E-2414
Performance cores

4
Processor Boost Frequency
4.5 GHz
Processor cache
12 MB
Thermal Design Power (TDP)
55,000
Number of processor cores
4
memory
Buffered memory type
Unregistered (unbuffered)
ECC
Yes
Internal storage type
DDR5-SDRAM
Memory card slots
4x DIMM
Storage capacity
16 GB
Storage data transfer rate
5600 MT/s
Maximum RAM
128 GB
network
Ethernet/LAN
Yes
Ethernet interface type
Gigabit Ethernet
LAN controller
Broadcom 5720
cabling technology
10/100/1000Base-T(X)
Storage medium
Total storage capacity
2000 GB
Number of installed HDDs
1
HDD capacity
2000 GB
Maximum supported number of HDDs
3
RAID support
No
RAID Level
0, 1, 5, 6, 10, 50, 60
Supported Hard Disk Drive Sizes
3.5
HDD interface
SATA III
HDD speed
7200
Optical drive - type
No
HDD size
3.5
design
Housing type
Tower (3U)
Product color
Black
Operating conditions
Humidity during storage
5 - 95
Temperature range during storage
-40 - 65
Height during operation
0 - 3048
Height during storage
0 - 12000
Scope of delivery
Package contents
European Power Cord 220V
software
Compatible operating systems

Canonical Ubuntu Server LTS Microsoft Windows Server
with Hyper-V Red Hat Enterprise Linux SUSE Linux
Enterprise Server VMware ESXi
Installed operating system
No
CO2 footprint
Total carbon dioxide footprint (kg of CO2e)
1182
Total carbon emissions, with/without use phase (kg of
CO2e)
472.8
Total carbon emissions, standard deviation (kg of
CO2e)
924
Carbon emissions at end of life (kg of CO2e)
23.64
Carbon emissions, energy consumption (kg of CO2e)
709.2
Carbon emissions, production (kg of CO2e)
319.14
Carbon emissions, logistics (kg of CO2e)
130.02
energy
power supply
300,000
Support for redundant power supply
No
Number of installed redundant power supplies
1
Weight and dimensions
Width
132.52 mm
Height
332.5 mm
Other functions
Data transfer rate
6 Gbit/s
Bytes per sector
512n