

**SERVER DELL POWEREDGE R260 XEON E-2314/1X16GB/1X2TB/700W 3YR**

Naziv: SERVER DELL POWEREDGE R260 XEON E-2314/1X16GB/1X2TB/700W 3YR

Slika:



Šifra: #BM512111766117307595

Barkod: EMEA\_PER260SPL1

Proizvođač: DELL

**Detalji**

Kategorija: SERVERI

Oznake: [Proveri dostupnost](#)

Atributi:

**Cena**

Cena sa PDV: 303,184.00 RSD \*WEB CENA  
333,502.40 RSD \*Cena za odloženo web plaćanje

**Ostalo**

Opis:

**specification**

Connections and interfaces

Number of USB 2.0 ports

2

Number of Ethernet LAN ports (RJ-45)

2

Number of VGA (D-Sub) ports

1

USB 3.2 Gen 1 (3.1 Gen 1) Number of Type A ports

1

Number of serial ports

1

Number of power cables

1

processor

Processor manufacturer

Intel

Processor family

Intel Xeon E

Processor threads

4

Processor clock speed

2.6 GHz

Number of installed processors

1

processor  
E-2414  
Performance cores  
4  
Processor Boost Frequency  
4.5 GHz  
Processor cache  
12 MB  
Thermal Design Power (TDP)  
55,000  
Number of processor cores  
4  
Services  
Remote Management  
iDRAC9 Basic 16G  
Trusted Platform Module (TPM)  
Yes  
network  
Ethernet/LAN  
Yes  
Ethernet interface type  
Gigabit Ethernet  
LAN controller  
Broadcom 5720  
cabling technology  
10/100/1000Base-T(X)  
memory  
Buffered memory type  
Unregistered (unbuffered)  
ECC  
Yes  
Internal storage type  
DDR5-SDRAM  
Memory card slots  
4x DIMM  
Storage capacity  
16 GB  
Storage data transfer rate  
5600 MT/s  
Maximum RAM  
128 GB  
Storage medium  
Total storage capacity  
2000 GB  
Number of installed HDDs  
1  
HDD capacity  
2000 GB  
Maximum supported number of HDDs  
2  
RAID support  
No  
RAID Level  
0, 1, 5, 6, 10, 50, 60  
HDD interface  
SATA III  
HDD speed  
7200  
Hot-plug support  
Yes  
Optical drive - type  
No  
HDD size  
3.5  
design  
Housing type  
Rack (1U)  
Product color  
Black  
Bezel  
Yes  
Storage rails  
Yes  
Operating conditions  
Humidity during storage

5 - 95  
Temperature range during storage  
-40 - 65  
Height during operation  
0 - 3048  
Height during storage  
0 - 12000  
Scope of delivery  
Package contents  
Riser Config 1, Gen4 Riser, European Power Cord 220V  
Certificates  
80 Plus Certification  
80 PLUS Titanium  
CO2 footprint  
Total carbon dioxide footprint (kg of CO2e)  
950  
Total carbon emissions, with/without use phase (kg of CO2e)  
408.5  
PAIA version  
1.3.2, 2024  
Carbon emissions at end of life (kg of CO2e)  
9.5  
Carbon emissions, logistics (kg of CO2e)  
95  
Total carbon emissions, standard deviation (kg of CO2e)  
711  
Carbon emissions, production (kg of CO2e)  
304  
Carbon emissions, energy consumption (kg of CO2e)  
541.5  
software  
Compatible operating systems  
Canonical Ubuntu Server LTS Microsoft Windows Server  
with Hyper-V Red Hat Enterprise Linux SUSE Linux  
Enterprise Server VMware ESXi  
Installed operating system  
No  
energy  
power supply  
700,000  
Power supply - Input voltage  
200 - 240 V  
Support for redundant power supply  
No  
Number of main power supplies  
1  
Weight and dimensions  
Width  
482 mm  
Height  
42.8 mm  
Other functions  
Data transfer rate  
6 Gbit/s  
Bytes per sector  
512n