

NAS RACKSTATION SYNOLOGY RS822RP+ 1U/4BAY

Naziv: NAS RACKSTATION SYNOLOGY RS822RP+ 1U/4BAY

Slika:



Šifra: #BM3306861767067803456

Barkod: 4711174724758

Proizvođač: SYNOLOGY

Detalji

Kategorija: NAS

Oznake:

Atributi:

CenaCena sa PDV: 287,159.04 RSD *WEB CENA
315,874.94 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Spefikacija	<p>CPUCPU model AMD Ryzen V1500B CPU Quantity 1 CPU Core 4 CPU Architecture 64-bitni CPU frekvencija 2,2 GHz Hardware Encryption Engine</p> <p>DaMemorija Sistemska memorija 2 GB DDR4 ECC SODIMM Memorijski modul unaprijed instaliran 2 GB (2 GB x 1) Ukupni memorijski slotovi 2 Maksimalni kapacitet memorije 32 GB (16 GB x 2)</p> <p>Skladištenje Drive Bays 4 Maksimalno ležišta pogona sa jedinicom za proširenje 8 (RX418 x 1) Kompatibilni tip diska 3,5" SATA HDD2,5" SATA SSDHot Swapdisk Da</p> <p>Eksterni portovi RJ-45 1GbE LAN port 4 USB 3.2 Gen 1 Port* 2 Port za proširenje 1 Tip priključka za proširenje eSATA PCIe PCIe Expansion 1 x Gen3 x8 slot (x4 link) Izgled Form Factor (RU) 1U Veličina (visina x širina x dubina) 44 mm x 480 mm x 518,6 mm Težina 8,0 kg Podrška za instalaciju u stalak* 19" stalak sa 4 stupa (Synology Rail Kit - RKM114 / RKS-02) Beleška</p> <p>Komplet šina se prodaje zasebnoOstalo Sistemska ventilator 40 mm x 40 mm x 2 kom Režim brzine ventilatora Režim pune brzineCool ModeQuiet ModePower Recovery Da Nivo buke* 38,8 dB(A) Planirano uključivanje / isključivanje DaWake on LAN / WAN Dajedinica napajanja / adapter 150 vatiRedundantno napajanje DaAC ulazni napon napajanja 100 V do 240 V AC Frekvencija snage 50/60 Hz, jednofazni Potrošnja energije 47,69 W (Pristup)16,7 W (Hibernacija HDD-a) Britanska termalna jedinica 162,83 BTU/sat (pristup)57,02 BTU/sat (hibernacija HDD-a) Temperatura Radna temperatura 0°C do 35°C (32°F do 95°F) Temperatura skladištenja -20°C do 60°C (-5°F do 140°F) Relativna vlažnost 5% do 95% RH 5% do 95% RHCertifikat FCC, CE, BSMI, VCCI, RCM,UKCA,EAC,CCC, KC,ULŽivotna sredina Usklađen sa RoHS Sadržaj pakovanja Glavna jedinica X 1Paket dodatne opreme X 1Kabl za napajanje naizmjeničnom strujom X 2Vodič za brzu instalaciju X 1</p>
-------------	---