

MATIČNA PLOČA 1851 GIGABYTE B860 DS3H WIFI6E 1.0

Naziv: MATIČNA PLOČA 1851 GIGABYTE B860 DS3H WIFI6E 1.0

Slika:



Šifra: #BM811801768017787717

Barkod: 4719331867515

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

Atributi:

CenaCena sa PDV: 22,990.00 RSD *WEB CENA
25,289.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte B860 DS3H WIFI6E LGA1851 DDR5 ATX Matična ploča
Procesorsko podnožje (Socket)	Intel Socket 1851
Skup čipova (Chipset)	Intel B860
Podrška za procesore	Intel Core Ultra Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	Support for DDR5 9066(O.C)/8800(O.C) /8600(O.C) / 8400(O.C) /8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) / 7800(O.C) / 7600(O.C.) / 7400(O.C.) / / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400 / 5600 MT/s memory modules4 x

Podrška za memorije	DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Podrška za grafiku - portovi	Integrated Graphics Processor-Intel® HD Graphics support:- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60HzSupport for HDMI 2.1 version and HDCP 2.3.- 1 x DisplayPort, supporting a maximum resolution of 3840x2160 144Hz
Slotovi za proširenja	CPU:- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset:- 4 x PCI Express x16 slots, supporting PCIe 4.0 and running at x1 (PCIEX1_1~PCIEX1_4)
M.2 portovi	2x M.2 Socket 3
Čuvanje podataka - portovi	CPU:- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 5.0 x4/x2 SSD support) (M2A_CPU) Chipset:- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)- 4 x SATA 6Gb/s connectorsRAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	Intel Wi-Fi 6E AX211 (PCB rev. 1.0)- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands- BLUETOOTH 5.3- Support for 11ax 160MHz wireless standardRealtek Wi-Fi 6E RTL8852CE (PCB rev. 1.1)- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands- BLUETOOTH 5.3- Support for 11ax 160MHz wireless standard
Bluetooth	5.3
Zvuk (Audio)	Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channelYou can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.Support for S/PDIF Out
	Chipset:- 1 x USB Type-C port on the back panel, with USB 3.2 Gen

USB portovi	2x2 support- 1 x USB Type-C port with USB 3.2 Gen 1 support, available through the internal USB header- 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel- 2 x USB 3.2 Gen 1 ports available through the internal USB header- 4 x USB 2.0/1.1 ports on the back panel Chipset+USB 2.0 Hub:- 4 x USB 2.0/1.1 ports available through the internal USB headers
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port 1 x HDMI port 1 x DisplayPort 1 x USB Type-C port, with USB 3.2 Gen 2x2 support 1 x USB 3.2 Gen 2 Type-A port (red) 4 x USB 2.0/1.1 ports 1 x RJ-45 port 2 x antenna connectors (2T2R) 3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 1 x CPU fan/water cooling pump header 2 x system fan headers 2 x system fan/water cooling pump headers 3 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 1 x USB Type-C header, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x serial port header 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	ATX