

**SVIČ 10/100/1000 16-PORT CUDY GS1016EPS2 LIGHT MANAGED POE+ SA 2X SFP 200W**Naziv: SVIČ 10/100/1000 16-PORT CUDY GS1016EPS2 LIGHT  
MANAGED POE+ SA 2X SFP 200W

Slika:



Šifra: #BM2726851769745756054

Barkod: 6971690794750

Proizvođač: CUDY

**Detalji**

Kategorija: SVIČEVI

Oznake: [Proveri dostupnost](#)

Atributi:

**Cena**Cena sa PDV: 23,990.00 RSD \*WEB CENA  
26,389.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

<b>Model Version</b>	GS1016EPS2 1.0
<b>1.25G SFP Slots</b>	2
<b>Gigabit RJ45 Ports</b>	16
<b>Gigabit RJ45 PoE Ports</b>	#1~#16
<b>Max Power on a Single PoE Port</b>	30W
<b>PoE Port Notes</b>	PoE ports comply with IEEE 802.3at/af standards
<b>PoE Priority</b>	Configurable; if no priority, smaller-numbered ports have higher priority
<b>Shielded RJ45 Port</b>	True
<b>Extend Mode Ports</b>	Configurable

<b>VLAN Mode Ports</b>	Configurable
<b>LED</b>	Power, PoE Status, Link/ACT, PoE Max Status
<b>Power Interfaces</b>	AC Inlet
<b>Physical Buttons</b>	Reset Button
<b>PoE Watchdog</b>	On/Off, customizable wait time in web management
<b>Copper Speed &amp; Distance</b>	Cat. 3+: 100 m @10 Mbps Cat. 5+: 100 m @100 Mbps Cat. 5e+: 100 m @1 Gbps Cat. 5e+: 250 m @10 Mbps (10 Mbps software-limited)
<b>Optical Spec &amp; Distance</b>	Depends on installed optical module
<b>MAC Address Table</b>	8192
<b>Max Switching Capacity</b>	36 Gbps
<b>Max Forwarding Rate</b>	26.78 Mpps
<b>Jumbo Frame</b>	15 KB
<b>Packet Buffer</b>	4 Mbit
<b>Power Methods</b>	AC
<b>Power Input</b>	100-240V~ 50/60Hz
<b>Power Supply</b>	200W
<b>Max Power Excluding PoE</b>	14W
<b>802.3 Protocols</b>	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X, 802.3x Flow Control, 802.3az Power Saving, 802.3af PoE, 802.3at PoE
<b>802.1 Protocols</b>	802.1p QoS, 802.1q VLAN, 802.1ab LLDP/LLDP-MED
<b>Port Management</b>	Port On/Off, Negotiation Speed, Port Trunk, Port Mirror, Data Rate Limit, Jumbo Frame Settings, Storm Control, Traffic Monitor, MAC Address Management, EEE
<b>PoE Management</b>	PoE Priority, PoE Watchdog On/Off, PoE Watchdog Period/Packet Threshold, PoE Consumed Power, PoE Standard, Delayed PoE Delivery, Total PoE Power Limit, PoE Power Limit
<b>Port Mirror Sessions</b>	4

<b>Port Trunk Groups</b>	4 (max 8 ports per group)
<b>L2 Features</b>	IGMP Snooping, Loop Prevention, DHCP Snooping, LLDP Config, MTU VLAN, Port-Based VLAN, 802.1Q VLAN, DSCP QoS, 802.1p QoS, Port-Based QoS
<b>Grounding Methods</b>	Three-Prong Plug, Grounding Point
<b>EMS</b>	IEC/EN 61000-4-2, Level 3 ESD; IEC/EN 61000-4-5, Level 4 Surge
<b>Operating Temperature</b>	0~40 °C (32~104 °F)
<b>Storage Temperature</b>	-40~70 °C (-40~158 °F)
<b>Operating Humidity</b>	10~90% non-condensing
<b>Storage Humidity</b>	10~95% non-condensing
<b>Control Methods</b>	Config Web Page, SNMP V1/V2
<b>Reliability</b>	Backup and Restore
<b>Diagnostic Tools</b>	Cable Status/Length Diagnosis, Ping
<b>Languages</b>	20+ including English, Spanish, Chinese, Arabic, etc.
<b>Dimensions</b>	440×220×44 mm (17.32×8.66×1.73 in)
<b>Product Weight</b>	2753.8 g (97.14 oz.)
<b>Casing Material</b>	Metal
<b>Installation</b>	Desktop, Rackmount via Brackets
<b>Package Content</b>	GS1016EPS2, Power Cord, Mounting Kit, Installation Guide