

SVIČ 10/100/1000 16-PORT CUDY GS1016EPS2 LIGHT MANAGED POE+ SA 2X SFP 200WNaziv: SVIČ 10/100/1000 16-PORT CUDY GS1016EPS2 LIGHT
MANAGED POE+ SA 2X SFP 200W

Slika:



Šifra: #BM2726851769745756054

Barkod: 6971690794750

Proizvođač: CUDY

Detalji

Kategorija: SVIČEVI

Oznake: [Proveri dostupnost](#)

Atributi:

CenaCena sa PDV: 23,990.00 RSD *WEB CENA
26,389.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model Version	GS1016EPS2 1.0
1.25G SFP Slots	2
Gigabit RJ45 Ports	16
Gigabit RJ45 PoE Ports	#1~#16
Max Power on a Single PoE Port	30W
PoE Port Notes	PoE ports comply with IEEE 802.3at/af standards
PoE Priority	Configurable; if no priority, smaller-numbered ports have higher priority
Shielded RJ45 Port	True
Extend Mode Ports	Configurable

VLAN Mode Ports	Configurable
LED	Power, PoE Status, Link/ACT, PoE Max Status
Power Interfaces	AC Inlet
Physical Buttons	Reset Button
PoE Watchdog	On/Off, customizable wait time in web management
Copper Speed & Distance	Cat. 3+: 100 m @10 Mbps Cat. 5+: 100 m @100 Mbps Cat. 5e+: 100 m @1 Gbps Cat. 5e+: 250 m @10 Mbps (10 Mbps software-limited)
Optical Spec & Distance	Depends on installed optical module
MAC Address Table	8192
Max Switching Capacity	36 Gbps
Max Forwarding Rate	26.78 Mpps
Jumbo Frame	15 KB
Packet Buffer	4 Mbit
Power Methods	AC
Power Input	100-240V~ 50/60Hz
Power Supply	200W
Max Power Excluding PoE	14W
802.3 Protocols	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X, 802.3x Flow Control, 802.3az Power Saving, 802.3af PoE, 802.3at PoE
802.1 Protocols	802.1p QoS, 802.1q VLAN, 802.1ab LLDP/LLDP-MED
Port Management	Port On/Off, Negotiation Speed, Port Trunk, Port Mirror, Data Rate Limit, Jumbo Frame Settings, Storm Control, Traffic Monitor, MAC Address Management, EEE
PoE Management	PoE Priority, PoE Watchdog On/Off, PoE Watchdog Period/Packet Threshold, PoE Consumed Power, PoE Standard, Delayed PoE Delivery, Total PoE Power Limit, PoE Power Limit
Port Mirror Sessions	4

Port Trunk Groups	4 (max 8 ports per group)
L2 Features	IGMP Snooping, Loop Prevention, DHCP Snooping, LLDP Config, MTU VLAN, Port-Based VLAN, 802.1Q VLAN, DSCP QoS, 802.1p QoS, Port-Based QoS
Grounding Methods	Three-Prong Plug, Grounding Point
EMS	IEC/EN 61000-4-2, Level 3 ESD; IEC/EN 61000-4-5, Level 4 Surge
Operating Temperature	0~40 °C (32~104 °F)
Storage Temperature	-40~70 °C (-40~158 °F)
Operating Humidity	10~90% non-condensing
Storage Humidity	10~95% non-condensing
Control Methods	Config Web Page, SNMP V1/V2
Reliability	Backup and Restore
Diagnostic Tools	Cable Status/Length Diagnosis, Ping
Languages	20+ including English, Spanish, Chinese, Arabic, etc.
Dimensions	440×220×44 mm (17.32×8.66×1.73 in)
Product Weight	2753.8 g (97.14 oz.)
Casing Material	Metal
Installation	Desktop, Rackmount via Brackets
Package Content	GS1016EPS2, Power Cord, Mounting Kit, Installation Guide