

SVIČ 10/100/1000 24-PORT CUDY GS1028EPS2 LIGHT MANAGED POE+ SA 2X SFP 200W

Naziv: SVIČ 10/100/1000 24-PORT CUDY GS1028EPS2 LIGHT MANAGED POE+ SA 2X SFP 200W

Slika:



Šifra: #BM2726851769745925777

Barkod: 6971690794736

Proizvođač: CUDY

Detalji

Kategorija: SVIČEVI

Oznake: [Proveri dostupnost](#)

Atributi:

Cena

Cena sa PDV: 32,990.00 RSD *WEB CENA
36,289.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:	Model Version	GS1028EPS2 1.0
	Gigabit RJ45/SFP Combo Ports	2
	Gigabit RJ45 Ports	26
	Gigabit RJ45 PoE Ports	#1~#24
	Max Power on a Single PoE Port	30W
	PoE Port Notes	PoE ports comply with IEEE 802.3at/af standards
	PoE Priority	Configurable; if no priority, smaller-numbered ports have higher priority
	Shielded RJ45 Port	True
	Extend Mode Ports	Configurable

VLAN Mode Ports	Configurable
LED	Power, PoE Status, Link/ACT, PoE Max Status
Power Interfaces	AC Inlet
Physical Buttons	Reset Button
PoE Watchdog	On/Off, customizable wait time in web management
Copper Speed & Distance	Cat. 3+: 100 m @10 Mbps Cat. 5+: 100 m @100 Mbps Cat. 5e+: 100 m @1 Gbps Cat. 5e+: 250 m @10 Mbps (10 Mbps software-limited)
Optical Spec & Distance	Depends on installed optical module
MAC Address Table	8192
Max Switching Capacity	56 Gbps
Max Forwarding Rate	41.664 Mpps
Jumbo Frame	15 KB
Packet Buffer	4 Mbit
Power Methods	AC
Power Input	100-240V~ 50/60Hz
Power Supply	300W
Max Power Excluding PoE	20W
802.3 Protocols	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X, 802.3x Flow Control, 802.3az Power Saving, 802.3af PoE, 802.3at PoE
802.1 Protocols	STP (802.1d), RSTP (802.1w), 802.1p QoS, 802.1q VLAN, LLDP/LLDP-MED
Port Management	Port On/Off, Negotiation Speed, Port Trunk, Port Mirror, Data Rate Limit, Jumbo Frame Settings, Storm Control, Traffic Monitor, MAC Address Management, EEE
PoE Management	PoE Priority, PoE Watchdog On/Off, PoE Watchdog Period/Packet Threshold, PoE Consumed Power, PoE Standard, Delayed PoE Delivery, Total PoE Power Limit, PoE Power Limit
Port Mirror	4

Sessions	.
Port Trunk Groups	4 (max 8 ports per group)
L2 Features	IGMP Snooping, Loop Prevention, DHCP Snooping, STP/RSTP, LLDP Config, MTU VLAN, Port-Based VLAN, 802.1Q VLAN, Voice VLAN, DSCP QoS, 802.1p QoS, Port-Based QoS
Fans	1 (Smart Cooling: adjusts based on power consumption)
Grounding Methods	Three-Prong Plug, Grounding Point
EMS	IEC/EN 61000-4-2, Level 3 ESD; IEC/EN 61000-4-5, Level 4 Surge
Operating Temperature	0~40 °C (32~104 °F)
Storage Temperature	-40~70 °C (-40~158 °F)
Operating Humidity	10~90% non-condensing
Storage Humidity	10~95% non-condensing
Control Methods	Config Web Page, SNMP V1/V2
Reliability	Backup and Restore
Diagnostic Tools	Cable Status/Length Diagnosis, Ping
Languages	20+ including English, Spanish, Chinese, Arabic, etc.
Dimensions	440×220×44 mm (17.32×8.66×1.73 in)
Product Weight	2941.2 g (103.75 oz.)
Casing Material	Metal
Installation	Desktop, Rackmount via Brackets
Package Content	GS1028EPS2, Power Cord, Mounting Kit, Installation Guide