

**MATIČNA PLOČA AM4 GIGABYTE A520M H RGB DVI/HDMI/M.2**Naziv: MATIČNA PLOČA AM4 GIGABYTE A520M H RGB  
DVI/HDMI/M.2

Slika:



Šifra: #BM811801775012814401

Barkod: 4719331879822

Proizvođač: GIGABYTE

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake:

Atributi: PROCESORSKO LEŽISTE: AM4  
CHIPSET: A520  
M.2: DA  
PODRŽANA MEMORIJA: DDR4**Cena**Cena sa PDV: 7,290.00 RSD \*WEB CENA  
8,019.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

Tip procesora	AMD
Podnožje	AMD&reg; AM4
Čipset	AMD&reg; A520
Format ploče	Micro ATX
Podržani procesori	AMD Socket AM4, support for: AMD Ryzen™ 5000 Series/ Ryzen™ 5000 G-Series/ Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors
Podržana memorija	DDR4
	2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Support for DDR4 5100(O.C.) / 4800(O.C.) / 4600(O.C.) / 4400(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C) / 3400(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz

Memorija	memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules* * ECC memory (ECC mode) support varies by CPU Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Slotovi za proširenje	CPU: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16 Chipset: 2 x PCI Express x1 slots, supporting PCIe 3.0
Storage	CPU: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 SATA and PCIe 3.0 x4/x2 SSD support) Chipset: 4 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, and RAID 10
Mrežna karta	Realtek® GbE LAN chip (1 Gbit/100 Mbit)
Zvučna karta	Realtek® Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
USB	CPU: 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 2 x USB 3.2 Gen 1 ports available through the internal USB header 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port 1 x DVI-D port 1 x HDMI port 4 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x Q-Flash Plus button 1 x RJ-45 port 3 x audio jacks
Interni konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 2 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x speaker header 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x serial port header 1 x chassis intrusion header 1 x Clear CMOS jumper
Bios	1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0