

MATIČNA PLOČA 1700 GIGABYTE H610I DDR5 2XDP/HDMI/VGA/M.2Naziv: MATIČNA PLOČA 1700 GIGABYTE H610I DDR5
2XDP/HDMI/VGA/M.2

Slika:



Šifra: #BM811801775098879534

Barkod: 4719331855222

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

Atributi:

CenaCena sa PDV: 18,990.00 RSD *WEB CENA
20,889.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte H610I DDR5 LGA1700 Mini ITX Matična ploča
Socket	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel H610
Podrška za procesore	Support for the 14th, 13th, and 12th Generation Intel Core, Pentium Gold and Celeron
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	2x 288-Pin DDR5
Podrška za memorije	13th Generation Intel Core i9/i7 Processors:- Support for DDR5 5600/5200/4800/4400 MT/s memory modules 13th Generation Intel Core i5/i3 and 12th Generation Intel Core, Pentium Gold and Celeron Processors:- Support for DDR5 4800/4400 MT/s memory module 2 x DDR DIMM sockets supporting up to

	64 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Podrška za grafiku - portovi	Integrated Graphics Processor-Intel HD Graphics support:- 1 x D-Sub port, supporting a maximum resolution of 1920x1200 60Hz- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version and HDCP 2.3. Support native HDMI 2.1 TMDS compatible ports.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz Support for DisplayPort 1.2 version and HDCP 2.3.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz
Slotovi za proširenja	1 x PCI Express x16 slot, running at x16(The PCIEX16 slot conforms to PCI Express 4.0 standard.)
M.2 portovi	1x M.2 Socket 3
Čuvanje podataka - portovi	Chipset:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 3.0 x4/x2 SSD support)- 4 x SATA 6Gb/s connectors
SATA portovi	4x SATA 6Gb/s
LAN	Intel GbE LAN chip (1 Gbps/100 Mbps)
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
USB portovi	Chipset: - 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)- 4 x USB 2.0/1.1 ports on the back panel Chipset+USB 2.0 Hub: - 2 x USB 2.0/1.1 ports available through the internal USB header
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse port 2 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x D-Sub port 2 x DisplayPorts 1 x HDMI port 1 x RJ-45 port 3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 1 x 4-pin ATX 12V power connector 1 x CPU fan header 1 x system fan header 1 x RGB LED strip header 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x speaker header 1 x USB 3.2 Gen 1 header 1 x USB 2.0/1.1 header 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) 1 x serial port header 1 x Clear CMOS jumper 1 x chassis intrusion header
	Support for APP Center- BIOS-

Posebne možnosti	EasyTune- Ambient LED- Smart Backup- System Information ViewerSupport for Q-FlashSupport for Xpress InstallVoltage detectionTemperature detectionFan speed detectionFan fail warningFan speed controlNorton Internet Security (OEM version)LAN bandwidth management software
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flashUse of licensed AMI UEFI BIOSPhP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Mini-ITX