

**MATIČNA PLOČA 1700 GIGABYTE H610I DDR5 2XDP/HDMI/VGA/M.2**Naziv: MATIČNA PLOČA 1700 GIGABYTE H610I DDR5  
2XDP/HDMI/VGA/M.2

Slika:



Šifra: #BM811801775098879534

Barkod: 4719331855222

Proizvođač: GIGABYTE

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake: NOVO

Atributi:

**Cena**Cena sa PDV: 18,990.00 RSD \*WEB CENA  
20,889.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

<b>Model</b>	Gigabyte H610I DDR5 LGA1700 Mini ITX Matična ploča
<b>Socket</b>	Intel Socket 1700 (LGA1700)
<b>Skup čipova (Chipset)</b>	Intel H610
<b>Podrška za procesore</b>	Support for the 14th, 13th, and 12th Generation Intel Core, Pentium Gold and Celeron
<b>Tip memorije (RAM)</b>	DDR5
<b>Broj memorijskih slotova</b>	2x 288-Pin DDR5
	13th Generation Intel Core i9/i7 Processors:- Support for DDR5 5600/5200/4800/4400 MT/s memory modules 13th Generation Intel Core i5/i3 and 12th Generation Intel Core, Pentium Gold and Celeron Processors:- Support for DDR5

<b>Podrška za memorije</b>	4800/4400 MT/s memory module2 x DDR DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
<b>Podrška za grafiku - portovi</b>	Integrated Graphics Processor-Intel HD Graphics support:- 1 x D-Sub port, supporting a maximum resolution of 1920x1200 60Hz- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60HzSupport for HDMI 2.1 version and HDCP 2.3.Support native HDMI 2.1 TMDS compatible ports.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60HzSupport for DisplayPort 1.2 version and HDCP 2.3.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz
<b>Slotovi za proširenja</b>	1 x PCI Express x16 slot, running at x16(The PCIEX16 slot conforms to PCI Express 4.0 standard.)
<b>M.2 portovi</b>	1x M.2 Socket 3
<b>Čuvanje podataka - portovi</b>	Chipset:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 3.0 x4/x2 SSD support)- 4 x SATA 6Gb/s connectors
<b>SATA portovi</b>	4x SATA 6Gb/s
<b>LAN</b>	Intel GbE LAN chip (1 Gbps/100 Mbps)
<b>Zvuk (Audio)</b>	Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channel
<b>USB portovi</b>	<b>Chipset:</b> - 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)- 4 x USB 2.0/1.1 ports on the back panel <b>Chipset+USB 2.0 Hub:</b> - 2 x USB 2.0/1.1 ports available through the internal USB header
<b>Konektori na zadnjoj strani</b>	1 x PS/2 keyboard/mouse port2 x USB 3.2 Gen 1 ports4 x USB 2.0/1.1 ports1 x D-Sub port2 x DisplayPorts1 x HDMI port1 x RJ-45 port3 x audio jacks
<b>Unutrašnji konektori</b>	1 x 24-pin ATX main power connector1 x 4-pin ATX 12V power connector1 x CPU fan header1 x system fan header1 x RGB LED strip header1 x M.2 Socket 3 connector4 x SATA 6Gb/s connectors1 x front panel header1 x front panel audio header1 x speaker header1 x USB 3.2 Gen 1 header1 x USB 2.0/1.1 header1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)1 x serial port header1 x Clear CMOS jumper1 x chassis intrusion header

<b>Posebne možnosti</b>	Support for APP Center- BIOS-EasyTune- Ambient LED- Smart Backup- System Information ViewerSupport for Q-FlashSupport for Xpress InstallVoltage detectionTemperature detectionFan speed detectionFan fail warningFan speed controlNorton Internet Security (OEM version)LAN bandwidth management software
<b>Operativni sistem</b>	Windows 10; Windows 11
<b>BIOS</b>	1 x 256 Mbit flashUse of licensed AMI UEFI BIOSPnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
<b>Format</b>	Mini-ITX