

MATIČNA PLOČA AM5 GIGABYTE B850M AORUS ELITE WF6E

Naziv: MATIČNA PLOČA AM5 GIGABYTE B850M AORUS ELITE WF6E

Slika:



Šifra: #BM811801781233429615

Barkod: 4719331871123

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NOVO

Atributi:

CenaCena sa PDV: 32,190.00 RSD *WEB CENA
35,409.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte B850M AORUS ELITE WIFI6E AM5 DDR5 Micro ATX Matična ploča
Socket	AMD Socket AM5
Skup čipova (Chipset)	AMD B850
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	Support for DDR5 8200(O.C.) / 8000(O.C.) / 7950(O.C.) / 7900(O.C.) / 7800(O.C.) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400(O.C.)

Podrška za memorije	/ 6200(O.C) / 6000(O.C) / 5800(O.C) / 5600(O.C) / 5200 / 4800 / 4400 MT/s memory modules.4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memoryDual channel memory architectureSupport for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Podrška za grafiku - portovi	Integrated Graphics Processor with AMD Radeon Graphics support:- 1 x DisplayPort, supporting a maximum resolution of 3840x2160 144HzSupport for DisplayPort 1.4 version and HDR.- 1 x Front HDMI port, supporting a maximum resolution of 1920x1080 30HzSupport for HDMI 1.4 version.
Slotovi za proširenja	1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x16 modeAMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 modeAMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 modeThe PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset:- 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4)
M.2 portovi	2x M.2 Socket 3
Čuvanje podataka - portovi	1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/22110/2580/2280 SSDs: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDsAMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDsAMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs 1 x M.2 connector (M2B_CPU), integrated in the CPU, supporting Socket 3, M key, type 22110/2280 SSDs: AMD Ryzen 9000/7000 Series Processors support PCIe 4.0 x4/x2 SSDsAMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDsAMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x2 SSDs4 x SATA 6Gb/s connectorsRAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devicesRAID 5 is only available on AMD Ryzen 9000 Series Processors.RAID 0, RAID 1, and RAID 10 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična	Realtek Wi-Fi 6E RTL8852CE- WIFI a, b, g, n, ac, ax, supporting 2,4/5/6

mreža	Support for 2.4/5 GHz carrier frequency bands
Bluetooth	5.3
Zvuk (Audio)	Realtek Audio CODEC (Only for rev. 1.0)High Definition Audio2/4/5.1/7.1-channelYou can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.Support for S/PDIF OutRealtek ALC1220 CODEC (Only for rev. 1.1)The back panel line out jack supports DSD audio.High Definition Audio2/4/5.1/7.1-channelYou can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.Support for S/PDIF Out
USB portovi	CPU :- 1 x USB Type-C port on the back panel, with USB 3.2 Gen 2 support- 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel CPU+USB 2.0 Hub :- 4 x USB 2.0/1.1 ports on the back panel Chipset+USB 3.2 Gen 1 Hub :- 4 x USB 3.2 Gen 1 ports on the back panel Chipset :- 1 x USB Type-C port with USB 3.2 Gen 2x2 support, available through the internal USB header- 3 x USB 3.2 Gen 1 ports (1 port on the back panel, 2 ports available through the internal USB header)- 4 x USB 2.0/1.1 ports available through the internal USB headers
Konektori na zadnjoj strani	1 x DisplayPort (Note)1 x Q-Flash Plus button4 x USB 2.0/1.1 ports5 x USB 3.2 Gen 1 ports2 x USB 3.2 Gen 2 Type-A ports (red)1 x USB Type-C port, with USB 3.2 Gen 2 support1 x RJ-45 port2 x antenna connectors (2T2R)2 x audio jacks1 x optical S/PDIF Out connector
Unutrašnji konektori	1 x 24-pin ATX main power connector1 x 8-pin ATX 12V power connector1 x CPU fan header1 x CPU fan/water cooling pump header3 x system fan headers1 x system fan/water cooling pump header3 x addressable RGB Gen2 LED strip headers1 x RGB LED strip header2 x M.2 Socket 3 connectors4 x SATA 6Gb/s connectors1 x front panel header1 x front panel audio header1 x USB Type-C header, with USB 3.2 Gen 2x2 support1 x USB 3.2 Gen 1 header2 x USB 2.0/1.1 headers1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)1 x HDMI port (Note)1 x reset button1 x reset jumper1 x Clear CMOS jumper
Posebne	Support for GIGABYTE Control Center (GCC)Support for Q-FlashSupport for Q-Flash PlusSupport for Smart

mogućnosti	BackupVoltage detectionTemperature detectionFan speed detectionWater cooling flow rate detectionFan fail warningFan speed control
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flashUse of licensed AMI UEFI BIOSPnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Micro ATX
Link ka proizvodjacu	https://www.gigabyte.com/