

MATIČNA PLOČA 1700 GIGABYTE B760M GAMING X DDR4 GEN5Naziv: MATIČNA PLOČA 1700 GIGABYTE B760M GAMING X
DDR4 GEN5

Slika:



Šifra: #BM811801782356746329

Barkod: 4719331874087

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NOVO

Atributi:

CenaCena sa PDV: 16,990.00 RSD *WEB CENA
18,689.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte B760M GAMING X DDR4 GEN5 LGA1700 ATX Matična ploča
Socket	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel B760
Podrška za procesore	Podrška za 14th, 13th, i 12th Generation Intel Core, Pentium Gold i Celeron Processors
Tip memorije (RAM)	DDR4
Broj memorijskih slotova	4x 288-Pin DDR4
	Podržani DDR4 moduli brzine 5333(O.C.) / 5133(O.C.) / 5000(O.C.) / 4933(O.C.) / 4800(O.C.) / 4700(O.C.) / 4600(O.C.) / 4500(O.C.) / 4400(O.C.) / 4300(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) /

Podrška za memorije	3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 3000 / 2933 / 2666 / 2400 / 2133 MT/s4 x DDR4 DIMM slota sa podrškom za do 128 GB sistemske memorije (do 32 GB po jednom DIMM modulu)Dvokanalna (dual-channel) arhitektura memorijePodrška za ECC unbuffered DIMM memorijske module tipa 1Rx8 / 2Rx8 (rade u non-ECC režimu)Podrška za non-ECC unbuffered DIMM memorijske module tipa 1Rx8 / 2Rx8 / 1Rx16Podrška za memorijske module sa Extreme Memory Profile (XMP) profilom(Konfiguracija procesora i memorije može uticati na podržane tipove memorije, brzinu prenosa podataka (brzinu) i broj DRAM modula. Za više informacija pogledajte „Memory Support List“ na sajtu kompanije GIGABYTE.)
Podrška za grafiku - portovi	Integrated Graphics Processor-Intel HD Graphics support:- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz
Slotovi za proširenja	CPU:- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset:- 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4)
M.2 portovi	2x M.2 Socket 3
Čuvanje podataka - portovi	CPU:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset:- 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)- 4 x SATA 6Gb/s connectorsRAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Zvuk (Audio)	Realtek Audio CODECHigh Definition Audio2/4/5.1/7.1-channelSupport for S/PDIF Out
USB portovi	Chipset:- 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header- 5 x USB 3.2 Gen 1 ports (3 ports on the back panel, 2 ports available through the internal USB header)- 1 x USB 2.0/1.1 port on the back panel Chipset+2 USB 2.0 Hubs:- 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)

Konektori na zadnjoj strani	3 x USB 3.2 Gen 1 ports 5 x USB 2.0/1.1 ports 2 x antenna connectors (2T2R) 1 x HDMI port (Note) 1 x DisplayPort (Note) 1 x RJ-45 port 3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 3 x system fan headers 3 x addressable LED strip headers 1 x RGB LED strip header 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 1 x USB Type-C header, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 2 x Thunderbolt add-in card connectors 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x serial port header 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Micro ATX
Link ka proizvođaču	https://www.gigabyte.com/