

MATIČNA PLOČA 1700 GIGABYTE B760M G XWF6E GEN5

Naziv: MATIČNA PLOČA 1700 GIGABYTE B760M G XWF6E GEN5

Slika:



Šifra: #BM811801783220561955

Barkod: 4719331872953

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NOVO

Atributi:

CenaCena sa PDV: 14,990.00 RSD *WEB CENA
16,489.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte B760M GAMING X WIFI6E GEN5 LGA1700 Micro ATX Matična ploča
Socket	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel B760
Podrška za procesore	Intel Core, Pentium Gold and Celeron Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	Support for DDR5 7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000 MT/s memory modules4 x DDR5 DIMM

Podrška za memorije	sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules (The CPU and memory configuration may affect the supported memory types, data rate (speed), and number of DRAM modules, please refer to "Memory Support List" on GIGABYTE's website for more information.)
Podrška za grafiku - portovi	Integrated Graphics Processor- Intel® HD Graphics support:- 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version and HDCP 2.3. Support native HDMI 2.1 TMDS compatible ports.- 1 x DisplayPort, supporting a maximum resolution of 4096x2304 60Hz Support for DisplayPort 1.2 version and HDCP 2.3
Slotovi za proširenja	CPU:- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16) The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. Chipset:- 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4)
M.2 portovi	2x M.2 Socket 3
Čuvanje podataka - portovi	CPU:- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset:- 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)- 4 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	Intel Wi-Fi 6E AX210- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands
Bluetooth	5.3
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings. Support for S/PDIF Out
	Chipset:- 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header- 5 x USB 3.2 Gen 1 ports (3 ports on

USB portovi	the back panel, 2 ports available through the internal USB header)- 1 x USB 2.0/1.1 port on the back panel Chipset+2 USB 2.0 Hubs:- 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	3 x USB 3.2 Gen 1 ports 5 x USB 2.0/1.1 ports 2 x antenna connectors (2T2R) 1 x HDMI port (Note) 1 x DisplayPort (Note) 1 x RJ-45 port 3 x audio jacks
Unutrašnji konektori	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 3 x system fan headers 3 x addressable LED strip headers 1 x RGB LED strip header 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 1 x USB Type-C header, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 2 x Thunderbolt add-in card connectors 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x serial port header 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup
Operativni sistem	Windows 10; Windows 11
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Micro ATX
Link ka proizvođaču	https://www.gigabyte.com/