

MB AM5 ASUS TUF GAMING B650M-PLUS

Naziv:

MB AM5 ASUS TUF GAMING B650M-PLUS

Slika:



Šifra:

#BM7611801784603114711

Barkod:

4711081912392

Proizvođač:

ASUS

Detalji

Kategorija:

MATIČNE PLOČE

Oznake:

Atributi:

PROCESORSKO LEŽIŠTE (SOCKET): AMD AM5
UKUPNO USB PRIKLJUČAKA: 8
TIP MEMORIJE: DDR5
MEMORIJSKI SLOTOVI: 4 X DDR5
MAKSIMALNA KOLIČINA MEMORIJE: 128
FORMAT: ATX

Cena

Cena sa PDV:

19,079.43 RSD *WEB CENA
20,987.37 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

Tip procesora	Procesorsko ležište (socket) AMD AM5 Čipset AMD® B650
Format ploče	Format micro ATX Dimenzije 244mm x 244mm
Memorija	Tip memorije DDR5 Memorijski slotovi 4x DDR5 Podržane memorije 5.400Mhz (O.C.), 6.000MHz (O.C.), 5.800MHz (O.C.), 5.600MHz (O.C.), 6.200MHz (O.C.), 4.800Mhz, 5.200Mhz, 5.000Mhz, 6.400MHz+ (O.C.) Maksimalna ukupna memorija 128GB Ostale osobine OptiMem II, Podrška za AMD EXTended Profiles for Overclocking (EXPO™), Dual Channel
Slotovi za proširenje	PCI Express x16 slot 1x PCI Express 4.0/3.0, 1x PCI Express 4.0/3.0 (x4 mode) PCI Express x1 slot 1x PCI Express 3.0 Skladišni interfejs

		SATA priključci (ukupno) 4 SATA priključci 4 x SATA 6Gb/s Ostali skladišni interfejs 2x M.2 RAID RAID 0, RAID 1, RAID 10
	Zvučna kartica	Broj kanala 8 (7.1) Model Realtek® Napomena Audio Shielding, Jack-detection, Multi-streaming, Front Panel Jack-retasking, Premium audio capacitors, Dedicated audio PCB layers
	Ostalo	Mreža Žična mreža (LAN) 1 x Realtek 2.5Gb Ethernet Priključci na zadnjem panelu DisplayPort priključci 1x DisplayPort HDMI priključci 1x HDMI Ukupno USB priključaka 8 Ukupno USB C priključaka 1 USB 3.2 priključci 2 (Tip A) Gen2, 1 (Tip C) Gen2x2, 1 (Tip A) Gen1 USB 2.0 priključci 4 (Tip A) RJ-45 (LAN) 1 Audio 5x 3.5mm Ostali priključci BIOS Flashback taster Unutrašnji priključci Naponski priključci 1 x 24 pin Main Power connector, 1 x 8-pin ATX 12V power connector, 1 x 4-pin ATX 12V power connector USB 3.2 1 (podrška za 2 USB 3.2 Gen 1 porta) USB 2.0 1 (podrška za 4 USB 2.0 porta) Audio 1x Front panel header Ostali priključci 1 x Clear CMOS header, 1 x front panel audio header, 1 x Thunderbolt header(s), 1 x 20-3 pin System Panel header with Chassis intrude function, 1 x 4-pin AIO Pump header, 1 x 4-pin CPU OPT Fan header, 1 x 4-pin CPU Fan header, 3 x Addressable Gen 2 headers, 1 x AURA RGB header, 1 x COM Port header, 3 x 4-pin Chassis Fan headers, 1 x M.2 slot (Key M) Napomena Za iskorišćavanje određenih internih konektora potrebni su dodatni bracket-i ili priključci na kućištu Ostale karakteristike Podržane tehnologije DIGI+VRM, Overvoltage Protection, Q-DIMM, Q-Slot, Aura RGB header, SafeDIMM, SafeSlot Core+, ProCool, Stainless-Steel Back I/O, Q-LED Core, BIOS FlashBack™ button, ESD Guards, TUF LANGuard, VRM heatsink design