

MB S1700 ASROCK B760 PRO RS 90-MXBKS0-A0UAYZ

Naziv: MB S1700 ASROCK B760 PRO RS 90-MXBKS0-A0UAYZ

Slika:



Šifra: #BM42511801791601348571

Barkod: 4710483942044

Proizvođač: ASROCK

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NOVO

Atributi: PROCESORSKO LEŽIŠTE (SOCKET): LGA1700
CHIPSET: B760
UKUPNO USB PRIKLJUČAKA: 13
TIP MEMORIJE: DDR5
MEMORIJSKI SLOTOVI: 4 X DDR5
MAKSIMALNA KOLIČINA MEMORIJE: 192
FORMAT: ATX

Cena

Cena sa PDV: 14,673.54 RSD *WEB CENA
16,140.89 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

- Unique Feature
Superb Productivity- PCIe Gen5 (Graphics)- Dual Channel DDR5**Rock-Solid Durability**- 10+1+1 Power Phase, 50A Dr.MOS for VCore+GT- Pre-Installed I/O Shield**Ultrafast Connectivity**- 2.5G LAN**EZ Update**- ASRock Auto Driver Installer**EZ Troubleshooter**- [ASRock Post Status Checker](#)
- CPU
 - Supports 14th, 13th & 12th Gen Intel® Core™ Processors (LGA1700)- Supports Intel® Hybrid Technology- Supports Intel® Turbo Boost Max 3.0 Technology- Supports Intel® Thermal Velocity Boost (TVB)- Supports Intel® Adaptive Boost Technology (ABT)
- Chipset
 - Intel® B760
- Memory
 - Dual Channel DDR5 Memory Technology- 4 x DDR5 DIMM Slots- Supports DDR5 non-ECC, un-buffered memory up to 7200+(OC)*- Max.

capacity of system memory: 256GB- Supports Intel® Extreme Memory Profile (XMP) 3.0
*1DPC 1R Up to 7200+ MHz (OC), 4800 MHz Natively.1DPC 2R Up to 6000+ MHz (OC), 4400 MHz Natively.2DPC 1R Up to 5600+ MHz (OC), 4000 MHz Natively.2DPC 2R Up to 4800+ MHz (OC), 3600 MHz Natively.

- BIOS
 - 128Mb AMI UEFI Legal BIOS with GUI support
- Graphics
 - Intel® Xe Graphics Architecture (Gen 12)- 1 x eDP 1.4, supports max. resolution up to Full HD 60Hz- 1 x HDMI 2.1 TMDS Compatible, supports HDCP 2.3 and max. resolution up to 4K 60Hz- 1 x DisplayPort 1.4 with DSC (compressed), supports HDCP 2.3 and max. resolution up to 8K 60Hz / 5K 120Hz
 - *Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.
- Audio
 - 7.1 CH HD Audio (Realtek ALC897 Audio Codec)- Nahimic Audio
- LAN
 - 2.5 Gigabit LAN 10/100/1000/2500 Mb/s- Dragon RTL8125BG- Supports Dragon 2.5G LAN Software-Smart Auto Adjust Bandwidth Control- Visual User Friendly UI- Visual Network Usage Statistics- Optimized Default Setting for Game, Browser, and Streaming Modes- User Customized Priority Control

Slots**CPU:-** 1 x PCIe 5.0 x16 Slot (PCIe1), supports x16 mode***Chipset:-** 1 x PCIe 4.0 x16 Slot (PCIe3), supports x4 mode*- 1 x PCIe 3.0 x16 Slot (PCIe4), supports x1 mode*- 1 x PCIe 3.0 x1 Slot (PCIe2)*- 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module and Intel® CNVio/CNVio2 (Integrated WiFi/BT)- Supports AMD CrossFire™*Supports NVMe SSD as boot disks**StorageCPU:-** 1 x Hyper M.2 Socket (M2_1, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode***Chipset:-** 1 x M.2 Socket (M2_2, Key M), supports type 2260/2280 PCIe Gen4x2 (32 Gb/s) mode*- 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*- 4 x SATA3 6.0 Gb/s Connectors*Supports Intel® Volume Management Device (VMD)Supports NVMe SSD as boot disks**RAID-** Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices**USB-** 2 x USB 3.2 Gen2 Type-C (1 Rear, 1 Front)- 1 x USB 3.2 Gen2 Type-A (Rear)- 6 x USB 3.2 Gen1 (4 Rear, 2 Front)- 4 x USB 2.0 (2 Rear, 2 Front)* All USB ports support ESD Protection**Connector-** 1 x eDP Signal Connector- 1 x SPI TPM Header- 1 x Power LED and Speaker Header- 2 x RGB LED Headers*- 2 x Addressable LED Headers*- 1 x CPU Fan Connector (4-pin)**- 1 x CPU/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)****- 5 x Chassis/Water Pump Fan Connectors (4-pin) (Smart Fan Speed Control)*****- 1 x 24 pin ATX Power Connector- 2 x 8 pin 12V Power Connectors (Hi-Density Power Connector)- 1 x Front Panel Audio Connector- 1 x Thunderbolt™ AIC Connector (5-pin) (Supports ASRock Thunderbolt™ 4 AIC Card)- 1 x USB 2.0 Header (Supports 2 USB 2.0 ports)- 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)- 1 x Front Panel Type C USB 3.2 Gen2 Header (10 Gb/s)*Support in total up to 12V/3A, 36W LED Strip**Support in total up to 5V/3A, 15W LED Strip***CPU_FAN1 supports the fan power up to 1A (12W).****CPU_FAN2/WP supports the fan power up to 2A (24W).*****CHA_FAN1~5/WP support the fan power up to 2A (24W).CPU_FAN2/WP and CHA_FAN1~5/WP can auto detect if 3-pin or 4-pin fan is in use.**Rear Panel I/O-** 2 x Antenna Mounting Points- 1 x HDMI Port- 1 x DisplayPort 1.4- 1 x USB 3.2

Gen2 Type-A Port (10 Gb/s)- 1 x USB 3.2 Gen2 Type-C Port (10 Gb/s)- 4 x USB 3.2 Gen1 Ports- 2 x USB 2.0 Ports- 1 x RJ-45 LAN Port- HD Audio Jacks: Line in / Front Speaker / Microphone Software and UEFI **Software**- ASRock Motherboard Utility (A-Tuning)- ASRock Dragon 2.5G LAN Software- ASRock Polychrome SYNC* **UEFI**- ASRock EZ Mode- ASRock Full HD UEFI- ASRock My Favorites in UEFI- ASRock Auto Driver Installer- ASRock Instant Flash- ASRock Easy RAID Installer*These utilities can be downloaded from ASRock Live Update & APP Shop. Accessories- 1 x User Manual- 2 x SATA Data Cables- 4 x Screws for M.2 Sockets- 1 x Standoff for M.2 Socket Form Factor- ATX Form Factor: 12.0-in x 9.6-in, 30.5 cm x 24.4 cm