

**MATIČNA PLOČA AM4 GIGABYTE B550M DS3H HDMI/DVI/M.2**Naziv: MATIČNA PLOČA AM4 GIGABYTE B550M DS3H  
HDMI/DVI/M.2

Slika:



Šifra: #BM811811725552917637

Barkod: 4719331809416

Proizvođač: GIGABYTE

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake:

Atributi: PROCESORSKO LEŽISTE: AM4  
CHIPSET: B550  
INTEGRISAN PROCESOR: DA  
M.2: DA  
PODRŽANA MEMORIJA: DDR4**Cena**Cena sa PDV: 12,990.00 RSD \*WEB CENA  
14,289.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

Tip procesora	AMD
Podnožje	AMD&reg; AM4
Čipset	AMD&reg; B550
Format ploče	Micro ATX
Podržani procesori	AMD podnožje AM4, podržava: 3rd Generation AMD Ryzen procesore/ 3rd Generation AMD Ryzen sa Radeon grafičkim procesorima
Podržana memorija	DDR4
	- 4 x DDR4 DIMM podnožje podržava do 128 GB (32 GB single DIMM capacity) sistemske memorije - 3rd Gen AMD Ryzen procesore: - Podržava DDR4 4400(O.C.) / 4000(O.C.) / 3600(O.C.) / 3333(O.C.) /3200/2933/2667/2400/2133 MHz memorijske module - 3rd Gen AMD

Memorija	Ryzen sa Radeon grafičkim procesorima: - Podržava DDR4 4733(O.C.) / 4600(O.C.) / 4400(O.C.) / 4000(O.C.) / 3600(O.C.) / 3333(O.C.) /3200/2933/2667/2400/2133 MHz memorijske module - Dual channel memory architecture - Podržava ECC Un-buffered DIMM 1Rx8/2Rx8 memorijske module - Podržava non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memorijske module - Podržava Extreme Memory Profile (XMP) memory modules
Integrirana grafička karta	Integrated in the 3rd Generation AMD Ryzen sa Radeon grafičkim procesorima: - 1 x DVI-D port, podržava maksimalnu rezoluciju od 1920x1200@60 Hz - DVI-D port ne podržava D-Sub konekciju putem adaptera - 1 x HDMI port, podržava maksimalnu rezoluciju od 4096x2160@60 Hz - Podržava HDMI 2.1 verziju, HDCP 2.3, i HDR - Maksimalna deljena memorija 16 GB
Slotovi za proširenje	1 x PCI Express x16 slot (PCIEX16), integrisan u CPU: - 3rd Generation AMD Ryzen procesora podržava PCIe 4.0 x16 mode - 3rd Generation AMD Ryzen sa Radeon grafičkim procesorima podržava PCIe 3.0 x16 mode 1 x PCI Express x16 slot (PCIEX4), integrisan u Chipset: - Podržava PCIe 3.0 x4 mode - 1 x PCI Express x1 slot (PCIEX1), integrisan u Chipset: - Podržava PCIe 3.0 x1 mode
Storage	- 1 x M.2 connector (M2A_CPU), integrisan u CPU, podržava podnožje 3, M key, tip 2242/2260/2280/22110 SSDs: - 3rd Generation AMD Ryzen procesora podržava SATA i PCIe 4.0 x4/x2 SSDs - 3rd Generation AMD Ryzen sa Radeon grafičkim procesorima podržava SATA i PCIe 3.0 x4/x2 SSDs - 1 x M.2 connector (M2B_SB), integrisan u Chipset, podržava podnožje 3, M key, tip 2242/2260/2280 SSDs: - Podržava SATA i PCIe 3.0 x2 SSDs - 4 x SATA 6Gb/s connectors, integrisani u Chipset: - Podržava RAID 0, RAID 1, i RAID 10
Mrežna karta	Realtek GbE LAN chip (1000 Mbit/100 Mbit)
Zvučna karta	- Realtek ALC887 codec - High Definition Audio - 2/4/5.1/7.1-channel
USB	CPU: - 4 x USB 3.2 Gen 1 porta na zadnjem panelu Chipset: - 2 x USB 3.2 Gen 1 porta dostupni putem internog USB headera - 6 x USB 2.0/1.1 portova (4 porta na zadnjem panelu, 2 porta dostupni putem internog USB headera)
Konektori na zadnjoj strani	- 1 x PS/2 keyboard/mouse port - 1 x DVI-D port - 1 x HDMI port - 4 x USB 3.2 Gen 1 ports - 4 x USB 2.0/1.1 ports - 1 x RJ-45 port - 3 x audio jacks
	- 1 x 24-pin ATX main power

Interni konektori	connector - 1 x 8-pin ATX 12V power connector - 1 x CPU fan header - 2 x system fan headers - 2 x addressable LED strip headers - 2 x RGB LED strip headers - 1 x CPU cooler LED strip/RGB LED strip header - 2 x M.2 Socket 3 connectors - 4 x SATA 6Gb/s connectors - 1 x front panel header - 1 x front panel audio header - 1 x USB 3.2 Gen 1 header - 1 x USB 2.0/1.1 header - 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) - 1 x serial port header - 1 x Clear CMOS jumper - 1 x Q-Flash Plus button
Bios	- 1 x 256 Mbit flash - Use of licensed AMI UEFI BIOS - PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0