

MATIČNA PLOČA AM5 GIGABYTE B650M AORUS ELITE AX ICE

Naziv: MATIČNA PLOČA AM5 GIGABYTE B650M AORUS ELITE AX ICE

Slika:



Šifra: #BM811811725553314419

Barkod: 4719331859336

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NEMA NA STANJU

Atributi: PROCESORSKO LEŽISTE: AM5
CHIPSET: B650
PODRŽANA MEMORIJA: DDR5**Cena**Cena sa PDV: 32,990.00 RSD *WEB CENA
36,289.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Procesorsko ležište (socket)	AMD AM5
Čipset	AMD B650
Format ploče	Micro ATX
Tip memorije	DDR5
Bluetooth	5.3
Podržani procesori	AMD Socket AM5, support for: AMD Ryzen™ 7000/ Ryzen™ 8000 Series Processors
Podržane memorije	Podržava DDR5 8000(OC) / 7800(OC) / 7600(OC) / 7200(OC) / 7000(OC) / 6800(OC) / 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s; 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory; Dual channel

	memory architecture; Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for AMD EXTended Profiles for Overclocking (AMD EXPO™) and Extreme Memory Profile (XMP) memory modules
Maksimalna ukupna memorija	192GB
Grafika	1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz
Slotovi za proširenje	CPU: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16) Chipset 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)
Skladište	CPU: 1 x M.2 connector (Socket 3, M key, type 25110/2280 PCIe 5.0 (Note) x4/x2 SSD support) (M2A_CPU) 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2B_CPU) Chipset: 4 x SATA 6Gb/s connectors RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices RAID 0, RAID 1, and RAID 10 support for SATA storage devices
Mrežna karta	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Zvučna karta	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
USB	CPU: 1 x USB Type-C® port on the back panel, with USB 3.2 Gen 2 support 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel CPU + USB 2.0 Hub: 4 x USB 2.0/1.1 ports on the back panel Chipset: 1 x USB Type-C® port with USB 3.2 Gen 2x2 support, available through the internal USB header 3 x USB 3.2 Gen 1 ports (1 port on the back panel, 2 ports available through the internal USB header) 4 x USB 2.0/1.1 ports available through the internal USB headers Chipset+USB 3.2 Gen 1 Hub: 4 x USB 3.2 Gen 1 ports on the back panel
Konektori na	1 x Q-Flash Plus button 2 x SMA antenna connectors (2T2R)jk 1 x DisplayPort 1 x HDMI port 1 x USB Type-C® port, with USB 3.2

Konektorji na zadnji strani	<p>Gen 2 support 2 x USB 3.2 Gen 2 Type-A ports (red) 5 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x RJ-45 port 1 x optical S/PDIF Out connector 2 x audio jacks</p>
Interni konektori (I/O)	<p>1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 1 x CPU fan/water cooling pump header 3 x system fan headers 1 x system fan/water cooling pump header 2 x addressable LED strip headers 2 x RGB LED strip headers 1 x CPU cooler LED strip/RGB LED strip header 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C® header, with USB 3.2 Gen 2x2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x serial port header 1 x THB_U4 add-in card connector 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/ GC-TPM2.0 SPI V2 module only) 1 x reset button 1 x reset jumper 1 x Clear CMOS jumper</p>
I/O kontroler	iTE® I/O Controller Chip
Bios	<p>1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0</p>
Reklamacioni period	24 meseca