

**MATIČNA PLOČA AM5 GIGABYTE B650M AORUS ELITE AX ICE**

Naziv: MATIČNA PLOČA AM5 GIGABYTE B650M AORUS ELITE AX ICE

Slika:



Šifra: #BM811811725553314419

Barkod: 4719331859336

Proizvođač: GIGABYTE

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake:

[Proveri dostupnost](#)

Atributi:

PROCESORSKO LEŽISTE: AM5  
CHIPSET: B650  
PODRŽANA MEMORIJA: DDR5**Cena**

Cena sa PDV:

31,270.00 RSD \*WEB CENA  
34,397.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

<b>Procesorsko ležište (socket)</b>	AMD AM5
<b>Čipset</b>	AMD B650
<b>Format ploče</b>	Micro ATX
<b>Tip memorije</b>	DDR5
<b>Bluetooth</b>	5.3
<b>Podržani procesori</b>	AMD Socket AM5, support for: AMD Ryzen™ 7000/ Ryzen™ 8000 Series Processors
<b>Podržane memorije</b>	Podržava DDR5 8000(OC) / 7800(OC) / 7600(OC) / 7200(OC) / 7000(OC) / 6800(OC) / 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s; 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory; Dual channel

	memory architecture; Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for AMD EXTended Profiles for Overclocking (AMD EXPO™) and Extreme Memory Profile (XMP) memory modules
<b>Maksimalna ukupna memorija</b>	192GB
<b>Grafika</b>	1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz
<b>Slotovi za proširenje</b>	CPU: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16) Chipset 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)
<b>Skladište</b>	CPU: 1 x M.2 connector (Socket 3, M key, type 25110/2280 PCIe 5.0 (Note) x4/x2 SSD support) (M2A_CPU) 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2B_CPU) Chipset: 4 x SATA 6Gb/s connectors RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices RAID 0, RAID 1, and RAID 10 support for SATA storage devices
<b>Mrežna karta</b>	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
<b>Zvučna karta</b>	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
<b>USB</b>	CPU: 1 x USB Type-C® port on the back panel, with USB 3.2 Gen 2 support 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel CPU + USB 2.0 Hub: 4 x USB 2.0/1.1 ports on the back panel Chipset: 1 x USB Type-C® port with USB 3.2 Gen 2x2 support, available through the internal USB header 3 x USB 3.2 Gen 1 ports (1 port on the back panel, 2 ports available through the internal USB header) 4 x USB 2.0/1.1 ports available through the internal USB headers Chipset+USB 3.2 Gen 1 Hub: 4 x USB 3.2 Gen 1 ports on the back panel
<b>Konektori na</b>	1 x Q-Flash Plus button 2 x SMA antenna connectors (2T2R)jk 1 x DisplayPort 1 x HDMI port 1 x USB Type-C® port, with USB 3.2

<b>Konektorji na zadnji strani</b>	<p>Gen 2 support  2 x USB 3.2 Gen 2 Type-A ports (red)  5 x USB 3.2 Gen 1 ports  4 x USB 2.0/1.1 ports  1 x RJ-45 port  1 x optical S/PDIF Out connector  2 x audio jacks</p>
<b>Interni konektori (I/O)</b>	<p>1 x 24-pin ATX main power connector  1 x 8-pin ATX 12V power connector  1 x CPU fan header  1 x CPU fan/water cooling pump header  3 x system fan headers  1 x system fan/water cooling pump header  2 x addressable LED strip headers  2 x RGB LED strip headers  1 x CPU cooler LED strip/RGB LED strip header  2 x M.2 Socket 3 connectors  4 x SATA 6Gb/s connectors  1 x front panel header  1 x front panel audio header  1 x USB Type-C® header, with USB 3.2 Gen 2x2 support  1 x USB 3.2 Gen 1 header  2 x USB 2.0/1.1 headers  1 x serial port header  1 x THB_U4 add-in card connector  1 x Trusted Platform Module header  (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/ GC-TPM2.0 SPI V2 module only)  1 x reset button  1 x reset jumper  1 x Clear CMOS jumper</p>
<b>I/O kontroler</b>	iTE® I/O Controller Chip
<b>Bios</b>	<p>1 x 256 Mbit flash  Use of licensed AMI UEFI BIOS  PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0</p>
<b>Reklamacioni period</b>	24 meseca