

**MATIČNA PLOČA GIGABYTE AM5 X870 EAGLE WIFI7**

Naziv: MATIČNA PLOČA GIGABYTE AM5 X870 EAGLE WIFI7

Slika:



Šifra: #BM811801731342549229

Barkod: 4719331864996

Proizvođač: GIGABYTE

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake:

Atributi:

**Cena**Cena sa PDV: 36,990.00 RSD \*WEB CENA  
40,689.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte X870 EAGLE WIFI7 AM5 DDR5 ATX Matična ploča
Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD X870
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
Podrška za	Support for DDR5 8200(OC) / 8000(OC) / 7800(OC) / 7600(OC) / 7200(OC) / 7000(OC) / 6800(OC) / 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s memory modules 4 x DDR5 DIMM sockets supporting up

memorije	<p>to 256 GB (64 GB single DIMM capacity) of system memory  Dual channel memory architecture  Support for non-ECC Un-buffered DIMM  1Rx8/2Rx8/1Rx16 memory modules  Support for AMD EXTended Profiles for Overclocking (AMD EXPO) and Extreme Memory Profile (XMP) memory modules</p>
Podrška za grafiku - portovi	<p>Integrated Graphics Processor with AMD Radeon Graphics support+ASMedia USB4 Controller:  - 2 x USB4 USB Type-C ports, supporting USB4 and DisplayPort video outputs and a maximum resolution of 3840x2160 240Hz  Support for DisplayPort 1.4 version and HDR.</p> <p>Integrated Graphics Processor with AMD Radeon Graphics support:  - 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz  Support for HDMI 2.1 version, HDCP 2.3, and HDR.  Support native HDMI 2.1 TMDS compatible ports.</p>
Slotovi za proširenja	<p>1 x PCI Express x16 slot (PCIEX16), integrated in the CPU:  AMD Ryzen 900/7000 Series Processors support PCIe 5.0 x16 mode  AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode  AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode  The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.</p> <p>Chipset:  - 2 x PCI Express x16 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_1/2)</p>
M.2 portovi	3x M.2 Socket 3
Čuvanje podataka - portovi	<p>1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/22110/2580/2280 SSDs:  AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs  AMD Ryzen 8000 Series- Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs  AMD Ryzen 8000 Series- Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs</p> <p>1 x M.2 connector (M2C_SB), integrated in the Chipset, supporting Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x2 SSDs</p> <p>1 x M.2 connector (M2B_SB), integrated in the Chipset, supporting Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSDs</p> <p>The M2B_SB connector shares bandwidth with the M2C_SB</p>

	<p>connector. The M2B_SB connector operates at up to x2 mode when a PCIe SSD is installed in the M2C_SB connector.</p> <p>4 x SATA 6Gb/s connectors RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices RAID 5 is only available on AMD Ryzen 9000 Series Processors.</p> <p>RAID 0, RAID 1, and RAID 10 support for SATA storage devices</p>
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	<p>MediaTek Wi-Fi 7 MT7925 (PCB rev. 1.0) - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard</p> <p>Realtek Wi-Fi 7 RTL8922AE (PCB rev. 1.1) - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard</p>
Bluetooth	5.4
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel
USB portovi	<p>CPU+ASMedia USB4 controller: - 2 x USB4 USB Type-C ports on the back panel</p> <p>CPU: - 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel - 1 x USB 3.2 Gen 1 port on the back panel</p> <p>CPU+USB 2.0 Hub: - 4 x USB 2.0/1.1 ports on the back panel</p> <p>Chipset: - 1 x USB Type-C port with USB 3.2 Gen 2x2 support, available through the internal USB header - 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) - 4 x USB 2.0/1.1 ports available through the internal USB headers</p>
Konektori na zadnjoj strani	<p>1 x Q-Flash Plus button 2 x antenna connectors (2T2R) 1 x HDMI port 2 x USB4 USB Type-C ports (DisplayPort) 1 x USB 3.2 Gen 2 Type-A port (red) 3 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks</p>
	<p>1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector</p>

Unutrašnji konektori	<ul style="list-style-type: none"> <li>1 x 4-pin ATX 12V power connector</li> <li>1 x CPU fan header</li> <li>1 x CPU fan/water cooling pump header</li> <li>4 x system fan headers</li> <li>3 x addressable RGB Gen2 LED strip headers</li> <li>1 x RGB LED strip header</li> <li>4 x SATA 6Gb/s connectors</li> <li>3 x M.2 Socket 3 connectors</li> <li>1 x front panel header</li> <li>1 x front panel audio header</li> <li>1 x USB Type-C header, with USB 3.2 Gen 2x2 support</li> <li>1 x USB 3.2 Gen 1 header</li> <li>2 x USB 2.0/1.1 headers</li> <li>1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)</li> <li>1 x power button</li> <li>1 x reset button</li> <li>1 x reset jumper</li> <li>1 x Clear CMOS jumper</li> </ul>
Posebne mogućnosti	<ul style="list-style-type: none"> <li>Voltage detection</li> <li>Temperature detection</li> <li>Fan speed detection</li> <li>Water cooling flow rate detection</li> <li>Fan fail warning</li> <li>Fan speed control</li> <li>Support for GIGABYTE Control Center (GCC)</li> <li>Support for Q-Flash</li> <li>Support for Q-Flash Plus</li> <li>Support for Smart Backup</li> </ul>
Operativni sistem	Windows 11
BIOS	<ul style="list-style-type: none"> <li>1 x 256 Mbit flash</li> <li>Use of licensed AMI UEFI BIOS</li> <li>PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0</li> </ul>
Format	ATX
Prava potrošača:	Zakonska saobraznost 2 godine
EAN:	4719331864996