


LAN ROUTER TP-LINK ARCHER C50 AC1200 2ANTENE EXT.

Naziv:	LAN ROUTER TP-LINK ARCHER C50 AC1200 2ANTENE EXT.
Slika:	
Šifra:	#BM4366901732377736540
Barkod:	6935364081065
Proizvođač:	TP-LINK

Detalji

Kategorija:	RUTERI
Oznake:	NOVO
Atributi:	TIP UREĐAJA: WIFI ROUTER TIP ANTENE: EXTERNA MESTO PRIMENE: INDOOR POE: NE BROJ PORTOVA: 5 4G/SIM SLOT: NE USB PORT: NE BRZINA PROTOKA: 750 MBPS - 1750 MBPS MESH: NE FREKVENTNI OPSEG: DUAL BAND REPEATER MODE: DA

Cena

Cena sa PDV:	4,649.00 RSD *WEB CENA 5,113.90 RSD *Cena za odloženo web plaćanje
--------------	---

Ostalo

Opis:	<table><tr><td colspan="2">WIRELESS</td></tr><tr><td>Standards</td><td>Wi-Fi 5 IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz</td></tr><tr><td>WiFi Speeds</td><td>AC1200 5 GHz: 867 Mbps (802.11ac) 2.4 GHz: 300 Mbps (802.11n)</td></tr><tr><td>WiFi Range</td><td>2 Bedroom Houses 4x Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas</td></tr></table>	WIRELESS		Standards	Wi-Fi 5 IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz	WiFi Speeds	AC1200 5 GHz: 867 Mbps (802.11ac) 2.4 GHz: 300 Mbps (802.11n)	WiFi Range	2 Bedroom Houses 4x Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas
WIRELESS									
Standards	Wi-Fi 5 IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz								
WiFi Speeds	AC1200 5 GHz: 867 Mbps (802.11ac) 2.4 GHz: 300 Mbps (802.11n)								
WiFi Range	2 Bedroom Houses 4x Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas								

	Medium
WiFi Capacity	Dual-Band Allocate devices to different bands for optimal performance
Working Modes	Router Mode Access Point Mode

HARDWARE	
Processor	Single-Core CPU
Ethernet Ports	1× 10/100 Mbps WAN Port 4× 10/100 Mbps LAN Ports
Buttons	WPS/Wi-Fi Button Power On/Off Button Reset Button
Power	9 V 0.85 A

SECURITY	
WiFi Encryption	WEP WPA WPA2 WPA/WPA2-Enterprise (802.1x)
Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway
Guest Network	1× 5 GHz Guest Network 1× 2.4 GHz Guest Network

SOFTWARE	
Protocols	IPv4 IPv6
Parental Controls	URL Filtering Time Controls
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP
Quality of Service	QoS by Device
NAT Forwarding	Port Forwarding Port Triggering DMZ UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	NO-IP DynDNS
Management	Tether App Webpage

PHYSICAL	
-----------------	--

PHYSICAL

Dimensions (W×D×H)	9.1 × 5.7 × 1.5 in (229.9 × 144.2 × 36.9 mm)
Package Contents	Wi-Fi Router Archer C50 Power Adapter RJ45 Ethernet Cable Quick Installation Guide

OTHER

System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access)
Certifications	FCC, CE, RoHS
Environment	Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

TEST DATA

WiFi Transmission Power	CE EIRP: <20dBm(2.4GHz) <23dBm(5GHz) FCC: <30dBm(2.4GHz & 5GHz)
WiFi Reception Sensitivity	5GHz: 11a 54M: -73dBm 11ac VHT20 MCS8: -68dBm 11ac VHT40 MCS9: -64dBm 11ac VHT80 MCS9: -60dBm 2.4GHz: 11g 54M: -76dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71dBm