

**LAN ROUTER TP-LINK TL-WR841N WIRELESS**

Naziv: LAN ROUTER TP-LINK TL-WR841N WIRELESS

Slika:



Šifra: #BM4366901732377846514

Barkod: 6935364051242

Proizvođač: TP-LINK

**Detalji**

Kategorija: RUTERI

Oznake:

[Proveri dostupnost](#)

Atributi:

TIP UREĐAJA: WIFI ROUTER  
TIP ANTENE: EXTERNA  
MESTO PRIMENE: INDOOR  
POE: NE  
BROJ PORTOVA: 5  
4G/SIM SLOT: NE  
USB PORT: NE  
BRZINA PROTOKA: 300 MBPS - 750 MBPS  
MESH: NE  
FREKVENTNI OPSEG: 2.4 GHZ  
REPEATER MODE: DA**Cena**

Cena sa PDV:

2,940.00 RSD \*WEB CENA  
3,234.00 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

<b>HARDWARE FEATURES</b>	
<b>Interface</b>	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
<b>Button</b>	Quick Setup Security Button Reset Button
<b>External Power Supply</b>	9VDC / 0.6A
<b>Wireless Standards</b>	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
<b>Antenna</b>	2*5dBi Fixed Omni Directional Antenna
<b>Dimensions (</b>	7.6 x 5.1 x 1.3 in.(192 x 130 x 33

<b>W x D x H )</b>	mm)
--------------------	-----

<b>WIRELESS FEATURES</b>	
<b>Frequency</b>	2.4-2.4835GHz
<b>Signal Rate</b>	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
<b>EIRP</b>	<20dBm(EIRP)
<b>Reception Sensitivity</b>	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
<b>Wireless Functions</b>	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
<b>Wireless</b>	64/128/152-bit WEP / WPA / WPA2, WPA-PSK / WPA2-PSK

<b>SOFTWARE FEATURES</b>	
<b>WAN Type</b>	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond
<b>DHCP</b>	Server, Client, DHCP Client List, Address Reservation
<b>Quality of Service</b>	WMM, Bandwidth Control
<b>Port Forwarding</b>	Virtual Server, Port Triggering, UPnP, DMZ
<b>Dynamic DNS</b>	DynDns, Comexe, NO-IP
<b>VPN Pass-Through</b>	PPTP, L2TP, IPSec (ESP Head)
<b>Access Control</b>	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
<b>Firewall Security</b>	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
<b>Management</b>	Access Control Local Management Remote Management

<b>OTHERS</b>	
<b>Certification</b>	CE, FCC, RoHS
<b>Package Contents</b>	Wireless N Router TL-WR841N Power supply unit Resource CD Quick Installation Guide
<b>System Requirements</b>	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
	Operating Temperature: 0~40°C

**Environment**

(32104)  
Storage Temperature: -40?70?  
(-40158)  
Operating Humidity: 10%90%  
non-condensing  
Storage Humidity: 5%90% non-  
condensing