

SERVER DELL POWEREDGE R250 XEON E-2314 4C 1X16GB 1X480GB PERC H355 450W 3YRNaziv: SERVER DELL POWEREDGE R250 XEON E-2314 4C
1X16GB 1X480GB PERC H355 450W 3YR

Slika:



Šifra: #BM512111732378006165

Barkod: 5902002250115

Proizvođač: DELL

Detalji

Kategorija: SERVERI

Oznake: NOVO

Atributi:

CenaCena sa PDV: 256,411.00 RSD *WEB CENA
282,052.10 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Basic data	
Item name	DELL PowerEdge R250 server 480 GB Rack (1U) Intel Xeon E E-2314 2.8 GHz 16 GB DDR4-SDRAM 450 W
Product symbol	emea_per250spl4
Hierarchy by CATEGORY	<ul style="list-style-type: none">Computers & PeripheralsComputersServers
Hierarchy by MANUFACTURER	<ul style="list-style-type: none">Dell
Package sizes (HxWxL)	250 x 600 x 920 mm
Weight gross	23 kg
Other features	
Data transfer rate	<ul style="list-style-type: none">6.00 Gb/s

Bytes per sector	<ul style="list-style-type: none"> • 512
Weight & dimensions	
Width	<ul style="list-style-type: none"> • 482.00 millimeter
Height	<ul style="list-style-type: none"> • 42.80 millimeter
Weight	<ul style="list-style-type: none"> • 12480.00 gram
Power	
Power cable length	<ul style="list-style-type: none"> • 2.00 meter
Power supply	<ul style="list-style-type: none"> • 450.00 W
Power cable current	<ul style="list-style-type: none"> • 10.00 A
Power cable connector 1	<ul style="list-style-type: none"> • C13 coupler
Power cable connector 2	<ul style="list-style-type: none"> • C14 coupler
Carbon footprint	
Total carbon footprint (kg of CO2e)	<ul style="list-style-type: none"> • 2100
icecat_automatic_47440_305	<ul style="list-style-type: none"> • 935
icecat_automatic_47441_305	<ul style="list-style-type: none"> • 505
Carbon emissions, logistics (kg of CO2e)	<ul style="list-style-type: none"> • 110
Carbon emissions, energy usage (kg of CO2e)	<ul style="list-style-type: none"> • 1470
icecat_automatic_47444_305	<ul style="list-style-type: none"> • 17
icecat_automatic_47445_305	<ul style="list-style-type: none"> • 632
icecat_automatic_47446_305	<ul style="list-style-type: none"> • 1.3.2, 2022
Software	
	<ul style="list-style-type: none"> • Canonical® Ubuntu® Server LTS Citrix®

Compatible operating systems	Hypervisor Microsoft® Windows Server® with Hyper-V RedHat® Enterprise Linux SUSE® Linux Enterprise Server VMware® ESXi®
Operating system installed	<ul style="list-style-type: none"> No
Design	
Chassis type	<ul style="list-style-type: none"> Rack (1U)
Product color	<ul style="list-style-type: none"> Black
Storage	
Supported RAID controllers	<ul style="list-style-type: none"> PERC H355
Optical drive type	<ul style="list-style-type: none"> No
Total storage capacity	<ul style="list-style-type: none"> 480.00 GB
SSD size	<ul style="list-style-type: none"> 2.5"
SSD interface	<ul style="list-style-type: none"> SATA III
SSD capacity	<ul style="list-style-type: none"> 480.00 GB
Supported SSD sizes	<ul style="list-style-type: none"> 3.5"
Network	
Ethernet interface type	<ul style="list-style-type: none"> Gigabit Ethernet
Cabling technology	<ul style="list-style-type: none"> 10/100/1000Base-T(X)
LAN controller	<ul style="list-style-type: none"> Broadcom 5720
Memory	
Memory clock speed	<ul style="list-style-type: none"> 3200.00 MHz
Internal memory	<ul style="list-style-type: none"> 16.00 GB
Maximum internal memory	<ul style="list-style-type: none"> 128.00 GB

Internal memory type	<ul style="list-style-type: none">• DDR4-SDRAM
Memory slots	<ul style="list-style-type: none">• 4x DIMM
Memory layout (slots x size)	<ul style="list-style-type: none">• 1 x 16 GB
Processor	
Processor frequency	<ul style="list-style-type: none">• 2.80 GHz
Processor cache	<ul style="list-style-type: none">• 8.00 MB
Processor manufacturer	<ul style="list-style-type: none">• Intel
Processor family	<ul style="list-style-type: none">• Intel Xeon E
Processor boost frequency	<ul style="list-style-type: none">• 4.50 GHz
Processor model	<ul style="list-style-type: none">• E-2314
Performance	
Remote administration	<ul style="list-style-type: none">• iDRAC9 Express 15G