PC BOOM

SAŠA BOŽOVIĆ PR USLUGE SISTEMA OBEZBEĐENJA PC BOOM BOOM BEDINA VAROŠ
32250 Ivanjica, 13. Septembar br.30
Tel: 060/386-09-09
E-mail: office@pcboomboom.rs

LAN SWITCH TP-LINK TL-SG1005P 10/100/1000 5PORT (4 POE)

Naziv:	LAN SWITCH TP-LINK TL-SG1005P 10/100/1000 5PORT (4 POE)
Slika:	
Šifra:	#BM4366851732696790779
Barkod:	6935364083212
Proizvođač:	TP-LINK

Detalji

Kategorija:	SVIČEVI
Oznake:	
Atributi:	

Cena

Cena sa PDV:	6,180.00 RSD *WEB CENA
	6,798.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

HARDWARE FEATURES	
Interface	• 5× 10/100/1000Mbps RJ45 Ports • AUTO Negotiation • AUTO MDI/MDIX
Network Media	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
External Power Supply	External Power Adapter (Output: 53.5 VDC / 1.31 A)
Packet Forwarding Rate	7.44 Mpps

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 65 W
Mac Address Table	2K
Jumbo Frame	16 KB
Switching Capacity	10 Gbps
Dimensions (W x D x H)	3.9×3.9×1.0 in (99.8×98×25 mm)
Max Power Consumption	• 4.29 W (220/50 Hz. no PD connected) • 74.24 W (220/50 Hz. with 65 W PD connected)
Max Heat Dissipation	• 14.63 BTU/h (no PD connected) • 253.16 BTU/h (with 65 W PD connected)

SOFTWARE FEATURES

Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Mac Address Auto-Learning And Auto-Aging • IEEE 802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping
Transfer Method	Store-And-Forward

OTHERS

Certification	FCC, CE, RoHS
Package Contents	• TL-SG1005P • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 ℃ (32–104 ℉); • Storage Temperature: -40–70 ℃ (-40–158 ℉) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing