

**MB AM4 ASUS AMD ROG STRIX B550-F GAMING**

Naziv: MB AM4 ASUS AMD ROG STRIX B550-F GAMING



Šifra: #BM7611801726042139588

Barkod: 4718017749688

Proizvođač: ASUS

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake: [Proveri dostupnost](#)

Atributi:

**Cena**Cena sa PDV: 23,424.00 RSD \*WEB CENA  
25,766.40 RSD \*Cena za odloženo web plaćanje

**Ostalo**

Opis:

Tip procesora:	AMD
Podnožje:	AMD® AM4
Čipset:	AMD® B550
Format ploče:	ATX
Podržana memorija:	DDR4
Podržani procesori:	- AMD AM4 podnožje 3rd Gen AMD Ryzen procesora
Memorija:	- 3rd Gen AMD Ryzen procesora - 4 x DIMM, Max. 128GB, DDR4 4600(O.C)/4400(O.C)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3600(O.C.)/3466(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered memoriju - Next Generation AMD Ryzen PRO procesora - 4 x DIMM, Max. 128GB, DDR4 5100(O.C)/4800(O.C.)/4600(O.C)/4400(O.C)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3600(O.C.)/3466(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered memoriju - Dual Channel Memory Architecture - OptiMem II - ECC Memory (ECC mode) podrška varira od CPU
Multi-GPU podrška:	- Podržava AMD 2-Way CrossFireX tehnologiju
Integrirana grafička karta:	Integrated Graphics Processor: - 1 x DisplayPort 1.2 - 1 x HDMI 2.1(4K@60HZ)
Slotovi za proširenje:	3rd Gen AMD Ryzen procesora - 1 x PCIe 4.0 x16 (x16 mode) AMD B550 Chipset - 1 x PCIe 3.0 x16 (x4 mode) - 3 x PCIe 3.0 x1
Skladište:	Maksimalno podržava 2 x M.2 slota i 6 x SATA 6Gb/s portova 3rd Gen AMD Ryzen procesora: - 1 x M.2_1 podnožje 3, sa M key, tip 2242/2260/2280/22110 storage uređaja (SATA & PCIe 4.0 x4 mode) AMD B550 Chipset: - 1 x M.2_2 podnožje 3, sa M key, tip 2242/2260/2280/22110 storage uređaja (SATA & PCIe 3.0 x 4 mode) - 6 x SATA 6Gb/s port(s) - Podržava Raid 0, 1, 10
Mrežna karta:	- Intel I225-V 2.5Gb Ethernet - ASUS LANGuard - ASUS Wi-Fi modul (Wi-Fi 802.11 a/b/g/n/ac i Bluetooth v5.0)
Zvučna karta:	ROG SupremeFX 8-Channel High Definition Audio CODEC S1220A - Dual OP Amplifiers - Impedance sense for front and rear headphone outputs - Podržava: Jack-detection, Multi-streaming, Front Panel Jack-retasking - High quality 120 dB SNR stereo playback output and 113 dB SNR recording input - Podržava i do 32-Bit/192kHz playback Audio Feature: - SupremeFX Shielding tehnologiju - Gold-plated jacks - Optical S/PDIF in port(s) na zadnjem panelu - Audio Shielding - Premium Japanese audio capacitors - Audio Cover
USB:	USB portovi sa zadnje strane ( Total 8 ) - 2 x USB 3.2 Gen 2 port(s)(1 x Type-A +1 x USB Type-C) - 4 x USB 3.2 Gen 1 port(s)(4 x Type-A) - 2 x USB 2.0 port(s) USB portovi sa prednje strane ( Total 6 ) - 2 x USB 3.2 Gen 1 port(s) - 4 x USB 2.0 port(s)
Konektori na zadnjoj strani:	- 1 x Intel I225-V 2.5Gb Ethernet - 1 x DisplayPort - 1 x HDMI - 2 x USB 3.2 Gen 2 (1 x Type-A+1 x USB Type-C) - 4 x USB 3.2 Gen 1 - 2 x USB 2.0 - 1 x Optical S/PDIF out - 1 x BIOS FlashBack Button(s) - 5 x Gold-plated audio jacks
Interni konektori:	- 1 x CPU Fan connector(s) - 1 x CPU OPT Fan connector(s) - 3 x Chassis Fan connector(s) - 1 x AIO_PUMP connector - 1 x AAFP connector - 2 x Aura RGB Strip Header(s) - 1 x Addressable Gen 2 header(s) - 1 x USB 3.2 Gen 1(up to 5Gbps) konektor podržava dodatna 2 USB 3.2 Gen 1 port(s) - 2 x USB 2.0 konektora podržavaju dodatna 4 USB 2.0 port(s) - 1 x M.2 podnožje 1 sa M key, tip 2242/2260/2280/22110 storage uređaja (SATA & PCIe 4.0 x4 mode) - 1 x M.2 podnožje 2 sa M key, tip 2242/2260/2280/22110 storage uređaja (SATA & PCIe 3.0 x 4 mode) - 6 x SATA 6Gb/s connector(s) - 1 x Thunderbolt header(s) - 1 x 24-pin EATX Power connector(s) - 1 x 8-pin ATX 12V Power connector(s) - 1 x 4-pin ATX 12V Power connector(s) - 1 x System panel(s) - 1 x Thermal sensor connector(s) - 1 x Clear CMOS jumper(s)