SAŠA BOŽOVIĆ PR USLUGE SISTEMA OBEZBEĐENJA PC BOOM BOOM BEDINA VAROŠ
32250 Ivanjica, 13. Septembar br.30
Tel: 060/386-09-09
E-mail: office@pcboomboom.rs

MB S1700 ASROCK B760M-HDV/M.2 D4 90-MXBL40-A0UAYZ

Naziv:	MB S1700 ASROCK B760M-HDV/M.2 D4 90-MXBL40-A0UAYZ
Slika:	
Šifra:	#BM42511801726042415723
Barkod:	4710483942020
Proizvođač:	ASROCK

Detalji

Kategorija:	MATIČNE PLOČE
Oznake:	Proveri dostupnost
Atributi:	

Cena

Cena sa PDV:	10,192.14 RSD *WEB CENA 11,211.35 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

- Unique Feature
  Rock-Solid Durability
  - 5+1+1 Power Phase
  EZ Update
  - ASRock Auto Driver Installer
- CPU
  - Supports 13th Gen & 12th Gen Intel® Core™ Processors (LGA1700)
  - Supports Intel® Hybrid Technology
  - Supports Intel® Turbo Boost Max 3.0 Technology
  - Supports Intel® Thermal Velocity Boost (TVB)
  - Supports Intel® Adaptive Boost Technology (ABT)
- Chipset
  - Intel® B760
- Memory
  - Dual Channel DDR4 Memory Technology
  - 2 x DDR4 DIMM Slots
  - Supports DDR4 non-ECC, un-buffered memory up to 5333+(OC)*
  - Supports ECC UDIMM memory modules (operate in non-ECC mode)
  - Max. capacity of system memory: 64GB*
  - Supports Intel® Extreme Memory Profile (XMP) 2.0

*1DPC 1R Up to 5333+ MHz (OC), 3200 MHz Natively.
1DPC 2R Up to 4400+ MHz (OC), 3200 MHz Natively.

- BIOS
  - 128Mb AMI UEFI Legal BIOS with GUI support
- Graphics
  - Intel® Xe Graphics Architecture (Gen 12)
  - 1 x HDMI 2.1 TMDS Compatible, supports HDCP 2.3 and max. resolution up to 4K 60Hz
  - 1 x DisplayPort 1.4 with DSC (compressed), supports HDCP 2.3 and max. resolution up to 8K 60Hz / 5K 120Hz
  - 1 x D-Sub, supports max. resolution up to Full HD (1920x1080) 60Hz

  *Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.
- Audio
  - 7.1 CH HD Audio (Realtek ALC887/897 Audio Codec)
- LAN
  - Gigabit LAN 10/100/1000 Mb/s
  - Realtek 8111H
- Slots
  CPU:
  - 1 x PCIe 4.0 x16 Slot (PCIE1), supports x16 mode*

  Chipset:
  - 2 x PCIe 3.0 x1 Slots (PCIE2 and PCIE3)*
  - 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module

  *Supports NVMe SSD as boot disks
- Storage
  CPU:
  - 1 x Hyper M.2 Socket (M2_1, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

  Chipset:
  - 1 x Ultra M.2 Socket (M2_2, Key M), supports type 2260/2280 SATA3 6.0 Gb/s & PCIe Gen3x4 (32 Gb/s) modes*
  - 4 x SATA3 6.0 Gb/s Connectors**

  *Supports Intel® Volume Management Device (VMD)
  Supports NVMe SSD as boot disks

  **If M2_2 is occupied by a SATA-type M.2 device, SATA3_3 will be disabled.
- RAID
  - Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices
- USB
  - 1 x USB 3.2 Gen1 Type-C (Rear)
  - 5 x USB 3.2 Gen1 Type-A (3 Rear, 2 Front)
  - 5 x USB 2.0 (2 Rear, 3 Front)

  * All USB ports support ESD Protection
- Connector
  - 1 x SPI TPM Header
  - 1 x Chassis Intrusion and Speaker Header
  - 1 x CPU Fan Connector (4-pin)*
  - 1 x CPU/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)**
  - 2 x Chassis/Water Pump Fan Connectors (4-pin) (Smart Fan Speed Control)***
  - 1 x 24 pin ATX Power Connector
  - 1 x 8 pin 12V Power Connector
  - 1 x Front Panel Audio Connector
  - 2 x USB 2.0 Headers (Support 3 USB 2.0 ports)
  - 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)

*CPU_FAN1 supports the fan power up to 1A (12W).

**CPU_FAN2/WP supports the fan power up to 2A (24W).
***CHA_FAN1~2/WP support the fan power up to 2A (24W).
CPU_FAN2/WP and CHA_FAN1~2/WP can auto detect if 3-pin or 4-pin fan is in use.

- Rear Panel I/O
  - 2 x Antenna Mounting Points
  - 1 x PS/2 Mouse/Keyboard Port
  - 1 x D-Sub Port
  - 1 x HDMI Port
  - 1 x DisplayPort 1.4
  - 1 x USB 3.2 Gen1 Type-C Port
  - 3 x USB 3.2 Gen1 Type-A Ports
  - 2 x USB 2.0 Ports
  - 1 x RJ-45 LAN Port
  - HD Audio Jacks: Line in / Front Speaker / Microphone
- Software and UEFI
  Software
  - ASRock Motherboard Utility (A-Tuning)
  - ASRock XFast LAN
  UEFI
  - ASRock EZ Mode
  - ASRock Full HD UEFI
  - ASRock My Favorites in UEFI
  - ASRock Auto Driver Installer
  - ASRock Instant Flash
  - ASRock Easy RAID Installer

  *These utilities can be downloaded from ASRock Live Update & APP Shop.
- Accessories
  - 1 x User Manual
  - 1 x I/O Shield
  - 2 x SATA Data Cables
  - 3 x Screws for M.2 Sockets
- Form Factor
  - Micro ATX Form Factor: 9.6-in x 7.9-in, 24.4 cm x 20.1 cm
- OS
  - Microsoft® Windows® 10 64-bit / 11 64-bit
- Certifications
  - FCC, CE
  - ErP/EuP ready (ErP/EuP ready power supply is required)