

**MB AM4 ASUS PRIME B550M-A**

Naziv: MB AM4 ASUS PRIME B550M-A  
Slika:



Šifra: #BM7611801726044203032  
Barkod: 4718017755528  
Proizvođač: ASUS

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake: NEMA NA STANJU

Atributi:

**Cena**

Cena sa PDV: 14,740.00 RSD \*WEB CENA  
16,214.00 RSD \*Cena za odloženo web plaćanje

**Ostalo**

Opis: **CPU**

AMD AM4 Socket for AMD Ryzen™ 5000 Series/ 5000 G-Series/ 4000 G-Series/ 3000 Series Desktop Processors \*  
\* Refer to [www.asus.com](http://www.asus.com) for CPU support list

**Chipset**

AMD B550

**Memory**

4 x DIMM, Max. 128GB, DDR4  
4866(O.C.)/4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4333(O.C.)/4266(O.C.)/4200(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3400(O.C.)/3333(O.C.)/3200(O.C.) MHz Un-buffered Memory \*  
Dual Channel Memory Architecture  
ECC Memory (ECC mode) support varies by CPU.  
\* Refer to [www.asus.com](http://www.asus.com) for the Memory QVL (Qualified Vendors Lists), and memory frequency support depends on the CPU types.

**Graphic**

1 x D-Sub  
1 x DVI-D  
1 x HDMI 2.1(4K@60HZ)  
\*Graphics specifications may vary between CPU types.

**Expansion Slots**

**AMD Ryzen™ 5000 Series/ 3000 Series Desktop Processors**  
1 x PCIe 4.0 x16 (x16 mode)  
**AMD Ryzen™ 5000 G-Series/ 4000 G-Series Desktop Processors**  
1 x PCIe 3.0 x16 (x16 mode)  
**AMD B550 Chipset**  
2 x PCIe 3.0 x1

**Storage**

**Total supports 2 x M.2 slot(s) and 4 x SATA 6Gb/s ports**  
**AMD Ryzen™ 5000 Series/ 3000 Series Desktop Processors :**  
1 x M.2\_1 socket 3, with M Key, Type 2242/2260/2280/22110(PCIE 4.0 x4 and SATA modes) storage devices support  
**AMD Ryzen™ 5000 G-Series/ 4000 G-Series Desktop Processors :**  
1 x M.2\_1 socket 3, with M Key, Type 2242/2260/2280/22110(PCIE 3.0 x4 and SATA modes) storage devices support  
**AMD B550 Chipset :**  
1 x M.2\_2 socket 3, with M Key, Type 2242/2260/2280 (PCIE 3.0 x4 and SATA modes) storage devices support  
4 x SATA 6Gb/s port(s),  
Support Raid 0, 1, 10

**LAN**

Realtek RTL8111H 1Gb Ethernet

**Audio**

Realtek ALC887/897 7.1 Surround Sound High Definition Audio CODEC  
- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback  
**Audio Feature :**  
- LED-illuminated design  
- Audio Shielding  
- Dedicated audio PCB layers  
- Premium Japanese audio capacitors  
\* Choose the chassis with HD audio module in front panel to support 8-channel audio output.

**USB Ports**

**Rear USB Port ( Total 6 )**  
2 x USB 3.2 Gen 2 port(s)(2 x Type-A)  
4 x USB 3.2 Gen 1 port(s)(4 x Type-A)  
**Front USB Port ( Total 6 )**

2 x USB 3.2 Gen 1 port(s)(2 x Type-A)  
4 x USB 2.0 port(s)(4 x Type-A)

## Software Features

ASUS Exclusive Software  
Armoury Crate  
- Aura Creator  
- Aura Sync  
AI Suite 3  
- Performance And Power Saving Utility  
TurboV EVO  
EPU  
Digi+ VRM  
Fan Xpert 2+  
- EZ update  
ASUS CPU-Z  
AI Charger  
DAEMON Tools  
Norton Anti-virus software (Free Trial for 60 days)  
WinRAR  
UEFI BIOS  
ASUS EZ DIY  
- ASUS CrashFree BIOS 3  
- ASUS EZ Flash 3  
- ASUS UEFI BIOS EZ Mode

## ASUS Special Features

ASUS 5X PROTECTION III  
- ASUS DIGI+ VRM  
- ASUS LANGuard  
- ASUS Overvoltage Protection  
- ASUS SafeSlot Core  
- ASUS Stainless-Steel Back I/O  
ASUS Q-Design  
- ASUS Q-DIMM  
- ASUS Q-Slot  
ASUS Thermal Solution  
- Aluminum heatsink design  
AURA Sync  
- Standard RGB headers  
- Addressable Gen 2 RGB header  
ASUS Lighting Control

## Back I/O Ports

1 x PS/2 keyboard/mouse combo port(s)  
1 x DVI-D  
1 x D-Sub  
1 x HDMI  
1 x LAN (RJ45) port(s)  
2 x USB 3.2 Gen 2 (teal blue) (2 x Type-A)  
4 x USB 3.2 Gen 1 (blue) Type-A  
3 x Audio jack(s)

## Internal I/O Ports

1 x CPU Fan connector(s)  
1 x CPU OPT Fan connector(s)  
2 x Chassis Fan connector(s)  
2 x Aura RGB Strip Headers  
1 x Addressable Gen 2 header(s)  
1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)  
2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)  
1 x M.2 Socket 3 with M Key, type 2242/2260/2280/22110 storage devices support (SATA mode & X4 PCIe mode)  
1 x M.2 Socket 3 with M Key, type 2242/2260/2280 storage devices support (SATA mode & X4 PCIe mode)  
1 x SPI TPM header  
4 x SATA 6Gb/s connector(s)  
1 x S/PDIF out header(s)  
1 x 24-pin EATX Power connector(s)  
1 x 8-pin EATX 12V Power connectors  
1 x Front panel audio connector(s) (AAFP)  
1 x Clear CMOS jumper(s)  
1 x System panel connector  
1 x COM port header  
1 x Speaker connector

## Accessories

I/O Shield  
2 x SATA 6Gb/s cable(s)  
1 x Supporting DVD  
User manual  
1 x M.2 SSD screw package(s)

## BIOS

256 Mb Flash ROM, UEFI AMI BIOS

## Manageability

WOL by PXE

## Operating System

Windows® 10 64-bit

## Form Factor

mATX Form Factor  
9.6 inch x 9.6 inch ( 24.4 cm x 24.4 cm )