

MB AM4 ASROCK A520M-HVS 90-MXBE60-A0UAYZ

Naziv: MB AM4 ASROCK A520M-HVS 90-MXBE60-A0UAYZ

Slika:



Šifra: #BM42511801726044205832

Barkod: 4710483932311

Proizvođač: ASROCK

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

Atributi:

CenaCena sa PDV: 7,666.00 RSD *WEB CENA
8,432.60 RSD *Cena za odloženo web plaćanje**Ostalo**

- Opis:
- CPU
 - Supports AMD AM4 Socket Ryzen™ 3000, 4000 G-Series and 5000 and 5000 G-Series Desktop Processors*
 - 6 Power Phase design
- *Not compatible with AMD Ryzen™ 5 3400G and Ryzen™ 3 3200G.
- Chipset
 - AMD A520
 - Memory
 - Dual Channel DDR4 Memory Technology
 - 2 x DDR4 DIMM Slots
 - AMD Ryzen series CPUs (Vermeer) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
 - AMD Ryzen series CPUs (Matisse) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
 - AMD Ryzen series APUs (Cezanne) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) /

3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*

- AMD Ryzen series APUs (Renoir) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*

- Max. capacity of system memory: 64GB**

- Supports Extreme Memory Profile (XMP) memory modules

- 15µ Gold Contact in DIMM Slots

- BIOS
 - 128Mb AMI UEFI Legal BIOS with GUI support
 - Supports "Plug and Play"
 - ACPI 5.1 compliance wake up events
 - Supports jumperfree
 - SMBIOS 2.3 support
 - CPU, CPU VDDCR_SOC, DRAM, VDDP Voltage Multi-adjustment
- Graphics
 - Integrated AMD Radeon™ Vega Series Graphics in Ryzen Series APU*
 - DirectX 12, Pixel Shader 5.0
 - Shared memory default 2GB. Max Shared memory supports up to 16GB.**
 - Dual graphics output: support D-Sub and HDMI ports by independent display controllers
 - Supports HDMI 2.1 with max. resolution up to 4K x 2K (4096x2160) @ 60Hz
 - Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz
 - Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI 2.1 Port (Compliant HDMI monitor is required)
 - Supports HDR (High Dynamic Range) with HDMI 2.1
 - Supports HDCP 2.3 with HDMI 2.1 Port
 - Supports 4K Ultra HD (UHD) playback with HDMI 2.1 Port
 - Supports Microsoft® PlayReady

*Actual support may vary by CPU

**The Max shared memory 16GB requires 32GB system memory installed.

- Audio
 - 7.1 CH HD Audio (Realtek ALC887/897 Audio Codec)
 - Supports Surge Protection
- LAN
 - PCIe x1 Gigabit LAN 10/100/1000 Mb/s
 - Realtek RTL8111H
 - Supports Wake-On-LAN
 - Supports Lightning/ESD Protection
 - Supports Energy Efficient Ethernet 802.3az
 - Supports PXE
- Slots
 - 1 x PCI Express 3.0 x16 Slot (PCIe2: x16 mode)*
 - 1 x PCI Express 3.0 x1 Slot

*Supports NVMe SSD as boot disks

- Storage
 - CPU:
 - 1 x Ultra M.2 Socket (M2_1, Key M), supports type 2242/2260/2280 SATA3 6.0

Gb/s & PCIe Gen3x4 (32 Gb/s) modes*
Chipset:

- 4 x SATA3 6.0 Gb/s Connectors

*Supports NVMe SSD as boot disks
Supports ASRock U.2 Kit

- o RAID
 - Supports RAID 0, RAID 1 and RAID 10 for SATA storage devices
- o Connector
 - 1 x SPI TPM Header
 - 1 x COM Port Header
 - 1 x Chassis Intrusion and Speaker Header
 - 1 x CPU Fan Connector (4-pin)*
 - 2 x Chassis Fan Connectors (4-pin) (Smart Fan Speed Control)**
 - 1 x 24 pin ATX Power Connector
 - 1 x 4 pin 12V Power Connector
 - 1 x Front Panel Audio Connector
 - 2 x USB 2.0 Headers (Support 4 USB 2.0 ports) (Supports ESD Protection)
 - 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports) (Supports ESD Protection)

*The CPU Fan Connector supports the CPU fan of maximum 1A (12W) fan power.

**The Chassis Fan supports the water cooler fan of maximum 1A (12W) fan power.
CHA_FAN2 can auto detect if 3-pin or 4-pin fan is in use.

- o Rear Panel I/O
 - 1 x PS/2 Mouse/Keyboard Port
 - 1 x D-Sub Port
 - 1 x HDMI Port
 - 2 x USB 2.0 Ports (Supports ESD Protection)
 - 4 x USB 3.2 Gen1 Ports (Supports ESD Protection)
 - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)
 - HD Audio Jacks: Line in / Front Speaker / Microphone