

MB AMD AM5 ASUS PRIME B650-PLUS

Naziv: MB AMD AM5 ASUS PRIME B650-PLUS

Slika:



Šifra: #BM7611801726044808238

Barkod: 4711081923381

Proizvođač: ASUS

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NEMA NA STANJU

Atributi:

CenaCena sa PDV: 24,071.00 RSD *WEB CENA
26,478.10 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Tip procesora	Procesorsko ležište (socket) AMD AM5 Čipset AMD® B650
Format ploče	Format ATX Dimenzije 305mm x 244mm
Memorija	Tip memorije DDR5 Memorijski slotovi 4x DDR5 Podržane memorije 5.400Mhz (O.C.), 6.000MHz (O.C.), 5.800MHz (O.C.), 6.200MHz (O.C.), 4.800Mhz, 5.200Mhz, 5.000Mhz, 6.400MHz+ (O.C.), 5.600MHz Maksimalna ukupna memorija 128GB Ostale osobine OptiMem II, Podrška za AMD EXTended Profiles for Overclocking (EXPO™), Dual Channel
Slotovi za proširenje	PCI Express x16 slot 1x PCI Express 4.0 (x16 mode), 1x PCI Express 4.0 (x4 mode) PCI Express x1 slot 2x PCI Express 4.0 Skladišni interfejs SATA priključci (ukupno) 4 SATA priključci 4 x SATA 6Gb/s Ostali skladišni interfejs 2x M.2 RAID RAID 0, RAID 1, RAID 10
Zvučna kartica	Broj kanala 2 (2.0) Napomena Audio Shielding, Jack-detection, Multi-streaming, Front Panel Jack-retasking, Premium audio capacitors, Dedicated audio PCB layers
Ostalo	Mreža Žična mreža (LAN) 1 x Realtek 2.5Gb Ethernet Model Realtek® Priključci na zadnjem panelu DisplayPort priključci 1x DisplayPort HDMI priključci 1x HDMI Ukupno USB priključaka 8 Ukupno USB C priključaka 4 USB 3.2 priključci 1 (Tip C) Gen2, 3 (Tip A) Gen2, 2 (Tip A) Gen1 USB 2.0 priključci 2 (Tip A) RJ-45 (LAN) 1 Audio 5x 3.5mm Ostali priključci BIOS Flashback taster, 1 x optical S/PDIF, 1 x V-M.2 slot (Key E) Unutrašnji priključci Naponski priključci 1x 8 pin 12V Power Connector, 1 x 24 pin Main Power connector USB 3.2 1 (podrška za 2 USB 3.2 Gen 1 porta), 1 (podrška za 1 USB 3.2 Gen 1 Tip C porta) USB 2.0 1 (podrška za 4 USB 2.0 porta) Audio 1x Front panel header Ostali priključci 4 x SATA 6Gb/s, 1 x Clear CMOS header, 1 x 20-3 pin System Panel header with Chassis intrude function, 1 x 4-pin AIO Pump header, 1 x 4-pin CPU OPT Fan header, 1 x 4-pin CPU Fan header, 3 x Addressable Gen 2 headers, 1 x AURA RGB header, 1 x Thunderbolt™ (USB4®) header, 1 x COM Port header, 3 x 4-pin Chassis Fan headers, 2 x M.2 slot (Key M)

