

**MB AM4 ASUS PRIME B450M-A II**

Naziv: MB AM4 ASUS PRIME B450M-A II



Šifra: #BM7611801726046072387

Barkod: 4718017924986

Proizvođač: ASUS

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake:

Atributi:

**Cena**Cena sa PDV: 9,959.00 RSD \*WEB CENA  
10,954.90 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

Podnožje	AMD® AM4
Čipset	AMD® B450
Tip procesora	AMD
Format ploče	Micro ATX
Podržani procesori	AMD AM4 Socket for 3rd/2nd/1st Gen AMD Ryzen /2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/Athlon with Radeon Vega Graphics Processors
Podržana memorija	DDR4
Memorija	3rd/2nd/1st Gen AMD Ryzen / 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/ Athlon with Radeon Vega Graphics Processors 4 x DIMM, Max. 128GB, DDR4 4400(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3400(O.C.)/3300(O.C.)/3200(O.C.)/3000(O.C.)/2800(O.C.)/2666/2400/2133 MHz Un-buffered Memory Dual Channel Memory Architecture ECC Memory (ECC mode) support varies by CPU.
Integrirana grafička karta	Integrated Graphics in the 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/ Athlon with Radeon Vega Graphics Processors 1 x D-Sub 1 x DVI-D 1 x HDMI 2.0b
Slotovi za proširenje	3rd/2nd/1st Gen AMD Ryzen Processors 1 x PCIe 3.0 x16 (x16 mode) 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics Processors 1 x PCIe 3.0 x16 (x8 mode) AMD Athlon with Radeon Vega Graphics Processors 1 x PCIe 3.0 x16 (x4 mode) AMD B450 chipset 2 x PCIe 2.0 x1
Skladište	Total supports 1 x M.2 slot(s) and 6 x SATA 6Gb/s ports 3rd/2nd/1st Gen AMD Ryzen™ / 2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode) Athlon™ with Radeon™ Vega Graphics Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA mode) 3rd/2nd/1st Gen AMD Ryzen™ / 2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics/ Athlon™ with Radeon™ Vega Graphics Processors : 2 x SATA 6Gb/s port(s), Support Raid 0, 1, 10 AMD B450 chipset : 4 x SATA 6Gb/s port(s), Support Raid 0, 1, 10
Mrežna karta	Realtek® RTL8111H ASUS LANGuard
Zvučna karta	Realtek ALC887/897 7.1-Channel High Definition Audio CODEC - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback Audio Feature : - LED-illuminated design - Audio Shielding - Dedicated audio PCB layers - Premium Japanese audio capacitors
USB	Rear USB Port ( Total 6 ) 2 x USB 3.2 Gen 2 (up to 10Gbps) port(s)(2 x Type-A) 4 x USB 3.2 Gen 1 port(s)(4 x Type-A) Front USB Port ( Total 6 ) 2 x USB 3.2 Gen 1 port(s) 4 x USB 2.0 port(s)
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse combo port(s) 1 x DVI-D 1 x D-Sub 1 x HDMI 1 x LAN (RJ45) port(s) 2 x USB 3.2 Gen 2 (teal blue) (2 x Type-A) 4 x USB 3.2 Gen 1 (blue) Type-A 3 x Audio jack(s) 1 x BIOS FlashBack Button(s)
Interni konektori	1 x CPU Fan connector(s) (1 x 4 -pin) 2 x Chassis Fan connector(s) (2 x 4 -pin) 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s) (19-pin) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s) 1 x M.2 Socket 3 with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode) 1 x SPI TPM header 1 x COM port(s) connector(s) 6 x SATA 6Gb/s connector(s) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) 1 x Clear CMOS jumper(s) 1 x COM port header 1 x Speaker connector 1 x RGB Header
BIOS	256 Mb Flash ROM, UEFI AMI BIOS